

1 channel  
Pan/Tilt Remote Controller

# CPT-130

## SPECIFICATION

<b>Control mode</b>	Left/ right, Up/down Auto/manual pan, driver switches
<b>Output connector</b>	Terminal 6pin, Standard Output power voltage Same as input power V
<b>Power switch</b>	Front panel , power LED indicator, Safety protection fuse: 1A
<b>Power voltage</b>	AC110V / AC220V option: (AC24V) , 50Hz/60Hz
<b>Casing structure</b>	Aluminum front panel, metal structure , color black
<b>Ambient temperature</b>	Operation -10°C ~ 50°C , Storage: -30°C ~ 70°C
<b>Body dimension</b>	1U ½Size : 210(W) ´ 44.5(H) ´ 240(D) mm – 1Kg



1 channel  
Zoom lens Remote Controller

# CPT-601

## SPECIFICATION

<b>Control mode</b>	Zoom in/out , Focus far/near , Iris open/close Iris auto/manual
<b>Lens control</b>	Lens voltage DC ± 8V ~ ± 12V / 150 mA internal adjustable
<b>Output Connector</b>	6 pin Terminal
<b>Power switch</b>	Front panel , Power LED indicator, Safety protection fuse: 0.5A
<b>Power voltage</b>	AC110V / AC220V Option (AC24V) , 50Hz/60Hz
<b>Casing Structure</b>	Aluminum front panel, metal structure, color black
<b>Ambient temperature</b>	operation: -10°C ~ 50°C , Storage: -30°C ~ 70°C
<b>Body Dimension</b>	1U ½Size 210(W) ´ 44.5(H) ´ 240(D) mm – 1Kg

