

1 channel
Pan/Tilt/Zoom Remote controller

CPT-1001K

SPECIFICATION

Control mode	Joystick: up / down, left / right Zoom in/out , Focus far/near , Iris open/close auto/manual pan , Iris auto/manual
Lens control	Lens voltage DC $\pm 8V \sim \pm 12V$ / 150 mA , internal adjustable
Terminal Connector	DIN 6p, Output power voltage same as input voltage, Lens: DIN 5p
Power switch	Front panel , Power LED indicator, Safety protection fuse 1A
Power voltage	AC110V / AC220V, Option(AC24V), 50Hz/60Hz
Casing Structure	Front panel, Metal structure, color black
Ambient temperature	Operation: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$, Storage: $-30^{\circ}\text{C} \sim 70^{\circ}\text{C}$
Body Dimension	1U 1/2Size 210(W) ´ 44.5(H) ´ 240(D) mm – 1.2 Kg



5 channels
Pan/Tilt/Zoom Remote controller

CPT-1005K

SPECIFICATION

Channel selection	Turner switching Joystick control: Up / Down, Left / Right
Control mode	Zoom in/out , Focus far/near , Iris open/close auto/manual pan
Lens control	Lens voltage: DC $\pm 8V \sim \pm 12V$ / 150 mA , Internal adjustable
Terminal Connector	DIN 6p, Output voltage same as input voltage, Lens: DIN 5p
Power switch	Front panel , Power LED indicator, Safety Fuse: 1A
Power voltage	AC110V / AC220V, Option (AC24V), 50Hz/60Hz
Casing Structure	Aluminum front panel, Metallic structure, color black
Ambient temperature	operation: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$, Storage: $-30^{\circ}\text{C} \sim 70^{\circ}\text{C}$
Body dimension	1U Full Size, 410(W) ´ 44.5(H) ´ 240(D) mm – 4 Kg

