# **Twisted Pair Transmission**



### AD001

#### **Video to VGA Converter**

- Special designed for CCTV color monitor,.
- Support NTSC M/N, PAL M/N, PAL, NTSC 4.43 and SECAM video system.
- Compact size, plug and play installation.
- On screen display function.
- Brightness, Contrast, Color, NTSC Tint Control.
- Resolution: NTSC: 640 x 480, PAL: 768 x 576.
- PAL, NTSC auto configure. (NTSC system for CRT/LCD monitor, PAL system for CRT monitor only).



#### **Hi Resolution Video to VGA Converter**

- Multi Signal inputs: VGA, Composite Vide, S-Video.
- Support NTSC, PAL video system.
- Input Video system 50-to-60HZ frame rate detection NTSC/PAL (SECAM) for Video, S-Video.
- The DEINTERLACED output mode: 800 x 600, 1024 x 768, up to 1280\*1024@60Hz.
- Frequency output: 60Hz, 70Hz, 75Hz, 85Hz.
- On screen display function: Contrast, Brightness, Color, Tint, Features, Resolution.



## **VD102**

## **CAT5 VGA 1 input to 2 Output Distributor**

- Each set including one piece VD102-T transmitter and one piece SP-A111VGA-R receiver.
- **Dual output:** 1 VGA loop output for local, plus 1 CAT5 RJ45 output for remote side.
- Use CAT5 cable instead of VGA cable.
- Long range transmission up to 300 meters (Max.)
- Built in contrast, brightness adjustment at Receiver.
- Supports up to 1600x1200 @85Hz.





