

# SCC-3100A

Mode		SCC-3100A
Power Source		12V DC, 700mA
Connector		3 Port
LCD Display		20 x 4 Character LCD
PTZ Control		Joystick (3-Axis twist zoom)
Sub Controller		Max. 16 unit connection
Control	PTZ Dome	SPD-3300/3000/2500/2300/2200/1600 PELCO-D, Panasonic (WV-CS854) SAMSUNG ELECTRONICS (SCC-643/641)
	DVR	SVR-1650E/1640/1630/950/430
	Receiver	SRX-100B
	Matrix	SMX-25632
Control Quantity		Max. 255
Auto Surveillance		Tour, Group, Swing, Preset etc. Selection of PTZ, DVR : Each ID input
Remote Control		RS-485/ RS-422 (Remote control 1.2Km above possibility)
RS-485/422 Spec.	Communication set	Asynchronism serial, 1 Start bit, No parity, 1 Stop bit
	Transmission method	Half duplex / Full duplex
	Baud Rate (bps)	4,800~38,400bps (9,600bps Promotion) Sub controller communication 56,400bps fixation
Operating Temperature		0 ~ 40°C
Operating Humidity		10 ~ 75%
Dimensions		400(W) x 180(H) x 88(D)mm
Weight		1.5Kg (Adapter exclusion)