

SDC-415

Mode	SDC-415ND	SDC-415NA	SDC-415PD	SDC-415PA	SDC-415PH
Power Source	12V DC ($\pm 10\%$)	24V AC ($\pm 10\%$)	12V DC ($\pm 10\%$)	24V AC ($\pm 10\%$)	230V AC ($\pm 10\%$)
Power Consumption	Max. 2.5W	Max. 3.5W	Max. 2.5W	Max. 3.5W	Max. 4.0W
Image Pick-up Device	1/3" Super HAD CCD				
Total Pixels	811(H) x 508(V)		795(H) x 596(V)		
Effective Pixels	768(H) x 494(V)		752(H) x 582(V)		
Scanning System	2 : 1 Interlace 525 Lines / 60 Fields / 30 Frames		2 : 1 Interlace 625 Lines / 50 Fields / 25 Frames		
Synchronization	Internal / Line lock selectable				
Scanning Frequency	Horizontal : 15,734KHz / Vertical : 59.94Hz		Horizontal : 15,625KHz / Vertical : 50Hz		
Horizontal Resolution	530TV lines (Min.)				
Video Output	1.0Vp-p / 75 Ω (Video 0.714Vp-p, Sync 0.286Vp-p)		1.0Vp-p / 75 Ω (Video 0.7Vp-p, Sync 0.3Vp-p)		
S / N Ratio (Y signal)	50dB (AGC off, Weight on)				
Min. Illumination	0.3Lux@F1.2 (Normal color mode) 0.002Lux@F1.2 (Sens-up mode)				
Back Light Compensation	Low / Middle / High / Off selectable				
Day & Night	On / Auto selectable (Electrical)				
Gain Control	Low / Middle / High / Off selectable				
White Balance	ATW / AWC / Manual selectable (1800°K ~ 10,500°K)				
Electronic Shutter Speed	Auto / Manual selectable (1/60 ~ 1/120,000sec)		Auto / Manual selectable (1/50 ~ 1/120,000sec)		
Sens-up	On / Off (Selectable limit 2X ~ 128X)				
OSD	Built-in				
SSNR	Low / Middle / High / Off selectable				
Motion Detection	On / Off selectable (4 Programmable zones)				
Privacy Function	On / Off selectable (4 Programmable zones)				
Iris Control	DC / Video				
Lens Mount	C / CS-mount (Easy focus type)				
Operating Temperature	-10°C ~ +50°C				
Operating Humidity	20% ~ 90% RH				
Dimensions	58(W) x 52(H) x 121(D)mm				
Weight	310g	340g	310g	340g	510g