

SLA-3580D/2985D/2810D/550D

| Mode | | SLA-3580D | SLA-2985D | SLA-2810D | SLA-550D |
|---------------------|------------|---------------------------|-----------------------------|---------------------------|-------------------------------|
| Focal Length | | 3.5 ~ 8mm | 2.9 ~ 8.5mm | 2.8 ~ 10mm | 5 ~ 50mm |
| Max. Aperture Ratio | | 1 : 1.4 ~ 360 | 1 : 1.2 ~ 360 | 1 : 1.4 ~ 360 | 1 : 1.8 ~ 360 |
| Max. Image Format | | 4.8(H) x 3.6(V) | | | |
| Operation | Iris | Auto (F1.4 ~ 360) | Auto (F1.2 ~ 300) | Auto (F1.4 ~ 360) | Auto (F1.4 ~ 360) |
| | Focus | Manual | | | |
| | Zoom | Manual | | | |
| Angle of View | Diagonal | 101.7° ~ 44.3° | 123.4° ~ 41.8° | 115.8° ~ 35.3° | 64.2° ~ 6.9° |
| | Horizontal | 80.7° ~ 35.4° | 96.2° ~ 33.4° | 93.7° ~ 28.3° | 51.7° ~ 5.5° |
| | Vertical | 60° ~ 26.5° | 70.7° ~ 25.1° | 70.6° ~ 21.2° | 38.9° ~ 4.1° |
| Iris Type | | DC | | | |
| Effective Lens | Front | Ø17.5mm | Ø21.14mm | Ø20.5mm | Ø37.7mm |
| | Rear | Ø8.8mm | Ø8.44mm | Ø8.8mm | Ø9.0mm |
| Back Focal Length | | 8.4 ~ 14.2mm | 7.95 ~ 15.3mm | 7.8 ~ 17mm | 7.6 ~ 11mm |
| Flange Back Length | | 12.5mm | | | |
| Mount | | CS-mount | | | |
| Dimensions | | 39(W) x 45(H) x 45.3(D)mm | 38.3(W) x 44.7(H) x 45(D)mm | 40(W) x 46(H) x 57.2(D)mm | 44.5(W) x 50.8(H) x 61.5(D)mm |
| Weight | | 57g | 50g | 65g | 140g |