

# SMX-25632

Mode	SMX-25632 (Matrix CPU)
System	16 Video card slots, Controller interface
Features	256 x 32 Video matrix control Video extension unit connector (up to 3 sets) Shake prevention when switching screens
OSD	Displays 16 Korean characters or 32 alphabet letters, numbers, or symbols Date / Time display
Camera I/O	64 camera input, 32 monitor output (Max. 32 Monitor output with 16 video cards)
Communication	TTL Level
Power Consumption	MAX. 120W
Operating Temperature	0°C ~ +40°C
Operating Humidity	30% ~ 90% RH
Dimensions	430(W) x 256(H) x 350(D)mm
Weight	15Kg
Mode	SME-25632 (Matrix Extension Bay)
Features	64 Camera input control (Connectable up to 3 units)
Power Consumption	MAX. 50W
Operating Temperature	0°C ~ +40°C
Operating Humidity	30% ~ 90% RH
Dimensions	430(W) x 177(H) x 350(D)mm
Weight	10Kg
Mode	SMV-25632 (Matrix Video Card)
Features	2 Monitor output Time generator, I/D generator, Video I/O selector, Video sync correction
OSD	32 Alphabet letters or 16 Korean characters (Combinations allowed) Freeze On / Off, Year / Month / Date / Hour / Minute / Second
Power Consumption	MAX. 9W
Operating Temperature	0°C ~ +40°C
Operating Humidity	30% ~ 90% RH
Dimensions	293.7(W) x 187(D)mm
Weight	0.3Kg