

# SNS-400

Mode	SNS-400 (NTSC)	SNS-400 (PAL)
Power Source	12V DC 1.5A	
Hardware OS	Embedded Linux	
Compression Method	MPEG-4 / JPEG selectable video compression, ADPCM audio compression	
Video Channel	4 Input / 1 output through BNC	
Compression / Transmission Speed	Video : Max. CIF 120fps	Video : Max. CIF 100fps
Image Quality Control	5 levels	
Audio Input / Output	4 / 1	
Motion Detection	4 Channel motion detection seperately	
Serial Connector	RS-232C / 422 / 485	
Transmission Interface	Ethernet (TCP/IP)	
Internet Browser	Windows internet explorer 5.5 or higher	
Resolution	704 x 480, 704 x 240, 352 x 240	704 x 576, 704 x 288, 352 x 288
Security	Password (User authentication), Control message encryption	
Back up	USB	
DIO Supports	4 Sensor input, 4 Alarm output	
Pan / Tilt / Zoom	Support	
User Connection	20 Users	
Protocol Supported	TCP/IP, DHCP, HTTP, SMTP, FTP, DDNS	
Misc. Function	Motion detection, Event / Alarm, FTP / E-mail notification	
Network Interface	10/100 Base-T ethernet using RJ-45, Static / Dynamic IP support	
Viewer Application	Network management Software / Web viewer	
DDNS	Support (xDSL, DHCP, Cable modem, etc)	
SDK	3rd Party SDK support	
Operating Temperature	0°C ~ 40°C	
Dimensions	185(W) x 45(H) x 125(D)mm	
Weight	805g	