

CAMERA ACCESSORIES

Housing & Bracket for Speed Dome Camera
(SPD-3300/3000/2300)

Mode	STH-330POV (Outdoor Housing)	STH-330PIV (Indoor Housing)	STH-320PO (Outdoor Housing)	STH-330PEV (Embedded Housing)	STB-270PWV (Wall Bracket)	STB-496PPV (Pendant Bracket)
Operating Temperature	-20°C - 50°C	-10°C - 50°C	-20°C - 50°C	-10°C - 50°C	-20°C - 50°C	-20°C - 50°C
Operating Humidity	0 to 90% RH	0 to 90% RH (non-condensing)	0 to 90% RH	0 to 90% RH (non-condensing)	0 to 90% RH (non-condensing)	0 to 90% RH (non-condensing)
Materials	Housing	ALDC 12	ALDC 10	EGI 1.2T	ALDC 12	ALDC 12
	Ring	ALDC 12	ALDC 12	ABS	EGI 1.2T	SPPS 32A/Sch 40
	Dome	Poly Carbonate	Poly Carbonate	-	-	SPCC
Antivibration / Waterproof	IP 67		IP 67	-	-	-
Dimensions	Ø242(W) x 284.5(H)mm		Ø243(W) x 281(H)mm	Ø235(W) x 188.5(H)mm	270(W) x 175(H) x 140(D)mm	150(W) x 496(H)mm
Weight	3.02Kg		1.55Kg	890g	1.2Kg	1.8Kg

Dimensions

Unit : mm

