

# SVR-1630

Mode		SVR-1630 (NTSC)	SVR-1630 (PAL)
Power Source		100-240V AC, 50/60Hz	
Power Consumption		Max. 75W (1 HDD)	
Video Input		16CH	
Video Output	Monitor A (Mux)	2 BNC, S-Video, VGA	
	Monitor B (Spot)	1 BNC	
Compression		Wavelet	
Display	Speed	480fps	400fps
	Resolution	720 x 480	720 x 576
	Multi Screen	1, 4, 9, 16	
Recording	Digital Zoom	2X	
	Speed	240fps	200fps
	Resolution	720 x 240	720 x 288
	Mode	Schedule, Event (Motion, Sensor, Text)	
HDD	Standard Installed	160GB / 250GB (Selectable)	
	Expand (Option)	2 HDDs (1 Internal, 1 R-HDD) Max. 4TB with HDD extension unit (SVR-1630S)	
Back up / Copy		R-HDD, IEEE-1394, USB, CD-RW (Option)	
External Interface		2 IEEE-1394, 1 USB	
Serial Interface		RS-485/422, RS-232C	
Text Data Recording with Images		POS / ATM	
Sensor Input / Relay Output		16 / 4	
Audio	Input / Output	1 CH / 1 CH	
Network	Interface	1 RJ-45 (10/100 Base-T)	
	Protocol	TCP/IP, DHCP, PPPoE	
	Software	SVR manager	
Control		Remote control (Controllable up to 16 DVRs)	
OSD (On Screen Display)		Multi-language	
Temperature	Operation	5°C - 40°C	
	Storage	-10°C - 50°C	
Dimensions		420(W) x 88(H) x 421(D)mm	
Weight		8Kg (1 HDD)	