

# SVR-440

Mode		SVR-440E (NTSC)	SVR-440E (PAL)
Power Source		12V DC (Adaptor)	
Power Consumption		Max. 25W	
Video Input		4CH	
Video Output		1 BNC, 1 VGA selectable	
Compression		MPEG-4	
Display	Speed /	30fps (D1, 704 x 480)	25fps (D1, 704 x 576)
	Resolution	120fps (CIF, 352 x 240)	100fps (CIF, 352 x 288)
	Multi Screen	1 / 4	
Recording	Speed	120fps	100fps
	Resolution	704 x 480, 352 x 240	704 x 576, 352 x 288
	Mode	Normal, Schedule, Event normal, Schedule, Event	
HDD		160GB	
Back up / Copy		USB (Front), External CD-RW (Option)	
Serial Interface		RS-485/422	
Sensor Input / Relay Output		4 / 1	
Audio	Input / Output	4 / 1	
Network	Interface	RJ-45 (10/100 Base-T)	
	Protocol	TCP/IP, DHCP, PPPoE	
	Software	Network viewer 440	
Control		Controllable upto 9 DVRs	
OSD (On Screen Display)		Stylish icon	
Temperature	Operation	5°C ~ 40°C	
Range	Storage	-10°C ~ 50°C	
Dimensions		350(W) x 65(H) x 260(D)mm	
Weight		3.2Kg	