

SVR-5116

Mode		SVR-5116 (NTSC)	SVR-5116 (PAL)
Power Source		100-240V AC, 50/60Hz	
Power Consumption		Max. 75W (1 HDD)	
Video Input		16CH	
Video Output		1 BNC, D-SUB (1 Multi spot + 8 Single spot), 1VGA, S-VGA	
Compression		MPEG-4	
Display	Speed	480fps	400fps
	Resolution	704 x 480, 704 x 240, 352 x 240	704 x 576, 704 x 288, 352 x 288
	Multi Screen	1 / 4 / 7 / 9 / 10 / 16	
Recording	Speed	120fps	100fps
	Resolution	704 x 480, 704 x 240, 352 x 240	704 x 576, 704 x 288, 352 x 288
	Mode	General (scheduled) recording, Event triggered recording and general + event triggered recording	
HDD		One 160GB hard drive (Max. 3 HDDs)	
Back up / Copy		CD-RW, 6 USBs (2 in front and 4 in back)	
Serial Interface		RS-485, RS-232C	
Alarm	Input / Output	16 / 16 TTL output	
Audio	Input / Output	1 / 1	
Network	Interface	RJ-45 (10/100 Base-T)	
	Protocol	TCP/IP, DHCP	
	Software	SVR manager, Web viewer	
OS		Windows XP	
CPU / RAM		P4 3.06GHz / 256MB	
Operating Temperature		5°C to 40°C	
Dimensions		482(W) x 177(H) x 449(D)mm	
Weight		14.7Kg	