

Industrial-Grade Media Converter


GNT-P2903AB

- Transmission Range: 20KM
- Transmission Rate: 100Mbps
- Power input: DC12-48V


Product Features

- PoE/Adapter Power Supply
- Aluminium Alloy Abrasive Material
- Convenient

Product Figure



Dimension (mm)



Installation Diagram



Specifications

Model	GNT-P2903AB
Protocol Standard	IEEE802.3/u
Network Interface	RJ45 10/100Mbps Self-Adaption
	Transmission Distance:100m
Fiber Interface	Single Mode SC
	Optical Fiber Type:Single Mode 9/125μm
	1310T/1550R (A) / 1550T/1310R (B)
	Transmission Rate:100Mbps
	Transmission Distance:≤20KM
Performance & Specification	Forwarding Mode:Store Forward
	Transfer Mode:Full Duplex/Full Duplex Automatic Connection
	Network Latency:≤150μs
Power	Power input: DC12-48V
	DC Socket:5525mm
Physical Specifications	Size:80*24*20mm, Weight: 0.09KG
Working Environment	Operating Temperature: -30°C~75°C
	Storage Temperature: -10°C~55°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Warranty	Whole Device: 1 year