

CONSIGLIO D'USO

Ambienti in cui viene richiesto un design raffinato

NORMA

EN1125

CARATTERISTICHE

Per porte di tutti i tipi e materiali

Reversibile

Fermo a giorno di serie

Dispositivo antiscasso

Disponibile anche nelle finiture di pregio: inox, oro, rame anticato




Per porte strette fino a 300 mm

Per porte alte fino a 2490 mm

Kit aste / scrocci, barra, comandi esterni da ordinare a parte

Comando esterno con cilindro intercambiabile con altri cilindri di sicurezza

Abbinabile agli incontri elettrici serie 16500



TESTO PER CAPITOLATI:

Maniglione antipanico con barra doppia funzione push (spingere) e pull (tirare) con sporgenza 66 mm. Applicabile su montanti di larghezza min. 55 mm., Millennium Nuova FEB.

APPLICATIONS

For areas where is required elegance

STANDARD

EN1125

FEATURES

For doors of all types and materials

Reversible

Hold - open device

Burglar-proof device

Top-class finishes also available: Stainless steel, gold, antiquated copper




For narrow doors of up to 300 mm

For high doors of height up to 2490 mm

Rod and latch kits, bars and outside access kits to be ordered separately

Outside access with cylinder interchangeable with other safety cylinders

Can be combined with electric strikers, 16500 series



TEXT FOR SPECIFICATIONS:

Panic bar with double action bar push and pull, with distance from the door 66 mm. To be fitted to narrow frames of min. width 55 mm., Nuova FEB Millennium

Articolo Article	Nota Note	Descrizione Description	Comandi esterni Outside access
19700		MILLENNIUM meccanismo base	
19700/B	micro-switch sul portabarra (B) micro-switch on bar holder (B)	MILLENNIUM mechanism	