

Motion sensor with wireless alert system, IP44, 120m

Marka: Orno | Symbol: OR-MA-717 | Ean: 5908254847851




PRODUCT DESCRIPTION

The sensor for monitoring entrances, hallways, warehouses, basements, driveways, car parks, etc. Each of the sensor has an indicator (receiver) which notifies, among other things, of detected movement or low batteries. The range in the open field is up to 120 m, while the motion detection range is up to 8 m. The sensor's viewing angle is approximately 75°. The IP44 rate allows to install the sensor outdoors and indoors, in rooms of increased humidity. The sensor is resistant to harsh weather conditions.

TECHNICAL DATA

General information:

Type of messaging:	Podczerwień pasywna
Mounting method:	Montaż powierzchniowy
Optical signaling:	Tak
Detection range [m]:	8
Communication range in open air [m]:	120
Detection Angle [°]:	75
Type of supply voltage - transmitter:	DC
Power Supply - transmitter [V]:	9
Battery type - transmitter:	6F22
Battery included:	Nie
Working current - transmitter [mA]:	< 10
Standby Current - transmitter [μA]:	< 20
Transmitter power [mW]:	≤ 10
Low Voltage Indicator - transmitter [V]:	<6,1 ± 0,1
Wireless Transmitting Frequency [MHz]:	433,92 ± 100
DC Voltage Input - receiver [V]:	6
DC Current Input - receiver [μA]:	≥ 500
Power Supply - receiver [V]:	4.5
Type of battery - receiver:	LR14 x3
Battery included:	Nie
Working current - receiver [mA]:	< 150
Standby Current - receiver [μA]:	< 500
Low Voltage Indicator - receiver [V]:	< 3,5 ± 0,1
Max. Alarm Volume [dB]:	90
Wireless Receiving Frequency [MHz]:	433,92 ± 100
Height transmitter [mm]:	111

Width transmitter[mm]:	69
Depth transmitter [mm]:	45
Height receiver [mm]:	130
Width receiver [mm]:	95
Depth receiver [mm]:	42
Colour:	Biały
Protection level IP:	IP44