







Marka: Virone | Symbol: VDP-72/W | Ean: 5908254848513

7", touch buttons, RFID reader, white





PRODUCT DESCRIPTION

The ANGU video doorphone set designed for single-family houses is a functional solution for entrance monitoring, thus increasing the safety of the user. It consists of an indoor monitor and an outdoor unit, which feature high-quality and modern design.

The device has an intuitive 4-wire connection that allows easy and reliable self-installation. Moreover, it reduces the number of cables running to the gate. The gate and door control increases the convenience of







use, and the electric strike does not require additional power supply.

The monitor is equipped with a 7-inch screen with a resolution of 800x480 px offering a clear, color image, as well as simple navigation thanks to sensor buttons. The wide viewing angle of the camera in the external panel (92° horizontally and 65° vertically) allows to monitor what is happening in front of the gate or door.

Additionally, the user can adjust the system to their individual preferences by selecting a ringtone from 12 melodies and adjusting the volume (including complete muting).

The monitor is made of white plastic. Designed for surface mounting. Dimensions: 185x127x24 mm.

The outdoor unit is equipped with a RFID card and key tag reader operating at a frequency of 13.56 MHz. It allows access for up to 200 users without the need to carry additional keys (two RFID key tags included).

The outdoor unit with IR lighting guarantees visibility at night, without blinding the visitor.

The high IP65 rate and the aluminium housing guarantee resistance to difficult weather conditions and protection against external damage. Silver colour. Designed for surface mounting. Compact dimensions of 54x139x33 mm allow the unit to be placed in narrow spaces.

The set may be expanded with one CCTV camera creating a complete monitoring system.

TECHNICAL DATA

General information:

Type:	jednorodzinny
With video:	tak
Current supply:	Zasilanie sieciowe
Nominal voltage [V]:	15V DC 2A
Type of transmission:	przewodowy
Can be connected to smartphone:	nie
Installation technique:	System wieloprzewodowy
Number of wires (*from outdoor unit to electric strike):	4 (+2)*
Number of indoor stations:	1
Number of outdoor stations:	1
Expandable to max. number of indoor stations:	1

Page 2 / 4

Update date: 2025-10-30 16:38:43









Expandable to max. number of outdoor stations:	1
Expandable to max. number of CCTV cameras:	1
Operation door lock:	tak
Current supply of the electric strike:	dodatkowy zasilacz niewymagany
Connection system of the electric strike:	z panelem zewnętrznym
With automatic door opener:	tak
With day/night function:	tak

Monitor:

Mounting method indoor station:	Montaż natynkowy
Hands free:	tak
Screen diagonal [inch]:	7"
Screen resolution:	800x480
Touch screen:	nie
Property picture system:	Kolor
With memory function:	nie
Internal communication:	nie
Number of ringtones:	12
Loudness control:	tak
Mutable call tone:	tak
Material indoor station:	Tworzywo sztuczne
Colour indoor station:	Biały
Dimensions of the monitor - Width [mm]:	185
Dimensions of the monitor - Height [mm]:	127
Dimensions of the monitor - Depth [mm]:	24

Outdoor unit:

Number of call buttons:	1
Mounting method outdoor station:	Montaż natynkowy









Camera resolution:	800TVL
Camera view angle:	92
Camera view angle:	65
Night light:	IR
With digital door code:	nie
Card and proximity tags reader:	tak
Frequency of RFID tags:	13,56MHz
Label space/information surface:	nie
With cover:	tak
Degree of protection (IP):	IP65
Material outdoor station:	Aluminium
Colour outdoor station:	Srebrny
Width [mm]:	54
Height [mm]:	139
Depth [mm]:	33
Other features:	RFID - max. 200 użytkowników (2 breloki w zestawie)