


AI PoE Switch



- 1 100Mbps PoE Ports
- 2 60W Power Ports
- 3 100Mbps Uplink Ports

GNT-P9206EA

Total 65W Power Supply
 4 ports PoE
 2 ports Uplink


Product Features

AI Watchdog Function
 6KV Lightning & 8KV ESD Protection
 Support bt 60W High Power
 Auto-Adaption 250m Transmission

Specifications

Ports	PoE (1~3):10/100Mbps PoE ports (RJ45) PoE (4):10/100Mbps PoE port (RJ45), Support bt 60W High Power LAN (1~2):10/100Mbps uplink ports (RJ45)
Transmission Rate	200Mbps Full Duplex; 10 or 100Mbps Half Duplex
Transmission Distance	100Mbps /10Mbps, Auto-Adaption 250m
Performance Specification	Bandwidth:1.2Gbps Network Latency (10 to 100Mbps): <= 16μs (use the 64byte package size) MAC address table: 2K The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port
Networking Standard	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x Flow Control IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 90~240V Total≤65W AI Watchdog: Port 1~4 Power Output: PoE1~3 Port:1/2(+52V),3/6(GND)≤30W PoE 4 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV, Per: IEC61000-4-5 ESD Protection:8KV, Per: IEC61000-4-2
Physical Specifications	Size(L*W*H): 187mm*139mm*43mm, Weight: 1.0KG
Working Environment	Operating Temperature: -30°C~60°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing
Certification	CE Mark FCC Part15, Class B RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC Power Cable, User Manual

Installation Diagram



Dimension (mm)

