

BSH-320IPBN-28

20m IR 2MP Fixed Lens Small Bullet Camera

This 2MP hybrid Bullet camera is made of aluminum alloy and polycarbonate. With it's hybrid capability, the white LED will enlighten the scene when humans being detected. it's designed for short-distance surveillance (up to 20m) in indoor and outdoor scenarios. With its excellent performance, reliability, and affordable price, the BSH-320IPBN-28 camera is the perfect solution for basic installations.



- 1/3 Sensor family
- 2.8 mm Lens
- PoE
- WDR Digital
- Build-In Mic
- IP67 Protection rating

- DDA 1 ANALYTICS
- Hybrid
- FACE DETECTION
- NDA
- FIXED LENS
- ONVIF S

MAIN FEATURES

- BSH-320IPBN-28
- Sensor: 1/3" CMOS (16:9)
- Resolution: 1920×1080 25/30FPS (2MP)
- Lens: 2.8mm (93°)
- True Day&Night – ICR
- Illumination: 20m (1 High-Power IR LED) 20m (1 High-Power White LED)
- Compression: H.265+ / H.264+ / H.265 / H.264 / MJPEG
- AI (Object Recognition): DDA Sterile Area, DDA Line Crossing Human only
- Digital WDR, BLC, HLC, ROI
- Built-in Microphone
- ONVIF: Profile S
- Water Proof: IP67
- Weight: ~300g
- Power: DC12V/~300mA / PoE/~4.5W



<https://provision-isr.com>

SPECIFICATIONS

| 3rd Party Cyber Protection | |
|----------------------------|---|
| General | N/A |
| Protection Methods | N/A |
| NDAA Compliant | |
| NDAA Compliant | Yes |
| Video | |
| Image Sensor | 1/3" CMOS (16:9) |
| Effective Pixels | 1920x1080 |
| Electronic Shutter | 1/3s ~ 1/100000s |
| Day & Night | ICR |
| Min. Illumination | Day: 0.2lux / Night: 0.046lux (@F2.2, AGC on) 0lux with IR on |
| Audio | |
| Audio compression | G.711A/G.711U |
| Communication | One-Way Audio |
| Image | |
| Image Settings | AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable |
| Image Enhancement | Digital WDR, BLC, HLC, ROI |
| Noise Reduction | 3D-DNR |
| Image Orientation | Mirror/Flip |
| Privacy Zone | Yes |
| Events and Analytics | |
| Analytics | AI (Object Recognition): DDA Sterile Area, DDA Line Crossing *Human only |
| Motion Detection | Yes |
| Compression | |

| | |
|--------------------------|---|
| Resolution | 2MP (1920x1080) / 1MP (1280x720) / D1 (704x576) / CIF (352x288) |
| Frame Rate | 1-25/30FPS |
| Video Compression | H.265+/ H.264+ / H.265 / H.264 / MJPEG** |
| Multi-Stream | Master Stream: 2MP (1920x1080) / 1MP (1280x720) (1~30fps) Substream: D1/CIF (1~30fps) |
| Bit Rate | 64Kbps ~ 4Mbps@H.265 / 64Kbps ~ 5Mbps@H.264 |
| Encode Mode | VBR/CBR |
| Image Quality | Five levels under VBR; Free adjustment under CBR |

| Lens | |
|-----------------------------|-------------|
| Lens (Field of View) | 2.8mm (93°) |
| Iris | Fixed Iris |
| Lens Mount | M12 Mount |
| Detect | 41m(133ft) |
| Recognize | 8m(26ft) |
| Identify | 4m(13ft) |

| Network | |
|--------------------------|---|
| User Access | Supports simultaneous monitoring of up to 3 users with multi-stream real-time transmission |
| Network Protocol | IPv4, IPv6, TCP, UDP, DHCP, NTP, 802.1X, RTSP, RTMP, Auto Report |
| Remote Monitoring | IE Browsing (Plug-In required), Chrome/Edge/Safari/Firefox plug-in free browsing, Ossia VMS Software, Provision Cam2 Mobile App |
| Ethernet | 100Mbps |
| ONVIF | Profile S |

| Connectivity | |
|---------------------------|---------------------|
| Network | RJ45 (+PoE) |
| Audio Connectivity | Built-in Microphone |

| | |
|----------------------------|-----------|
| Alarm | No |
| SD Card | No |
| Wiegand | No |
| Power | DC Socket |
| Analog Video Output | No |

| Housing | |
|--------------------------|--|
| PoE | Yes |
| Illumination | 20m (1 High-Power IR LED) 20m (1 High-Power White LED) |
| Power Supply | DC12V/~300mA / PoE/~4.5W |
| Protection Rate | Water Proof: IP67 |
| Work Environment | -30°C~60°C, 10%~90% Humidity |
| Bracket | 3-Axis Bracket |
| Dimensions | 172.2x73.4x74.5mm |
| Weight (gross) | ~300g |
| Hard Reset Button | No |