

# 4CH HD PASSIVE BALUN

PTR-401V-HD



<b>MODEL</b>	<b>PTR-401V-HD</b>	
Input	4Ch x Twisted Pair	
Output	4Ch BNC	
System Format	PAL / NTSC	
Input Resolution Support	5MP and Lower	
Input Signal Support	4 in 1 (AHD / CVI / TVI / CVBS)	
Transmission Distance	5MP	180m (AHD/TVI)
	4MP	180m (AHD/TVI)
	2MP	200m (AHD/TVI) / 230m (CVI)
	1MP	320m (AHD) / 250m (TVI) / 440m (CVI)
	960H and Lower	200m
Attenuation	1.5db Max	
Wiring	Unshielded Twisted Pair (Per Channel)	
Surge Protection	2KV	
Work Environment	-20°C-70°C, 0%-90% Humidity	
Power Source	Not Required (Passive Unit)	
Dimensions	100x72.5x23mm	
Net Weight	200g	

## Main Features:

- 4Ch Unit
- 5MP 4in1 support: AHD / CVI / TVI / CVBS
- Passive - No Power Required
- Surge Protection
- Minimal Attenuation
- Light Weight

## Technology max. distance

Technology / Resolution	AHD	CVI	TVI
720P	320m	440m	250m
1080P	200m	230m	200m
4MP	180m		180m
5MP	180m		180m

