

5CH HYBRID DVR

Analog: 4CH 960H Real-Time, IP: 1CH 1MP Non Real-Time

SA-4100SHX

960H 1MP



MODEL		SA-4100SHX	
System	Compression Format	High Profile H.264	
	ONVIF	Yes	
Video	Input	4CH Standard BNC + 1CH IP (Over Network)	
	Standard Output	VGA, CVBS (Spot), HDMI	
Audio	Input	2CH RCA + IPC Inputs Over Network	
	Output	1CH RCA + IPC Outputs Over Network	
	Two Way Audio	Yes	
Recording	Analog	Real-Time Recording	4CH 960H Real-Time
		960H	120FPS (NTSC)/100FPS (PAL)
		D1	120FPS (NTSC)/100FPS (PAL)
		CIF	120FPS (NTSC)/100FPS (PAL)
	IP	Real-Time Recording	1CH 1MP Non Real-Time
		3MP	No
		2MP	6FPS (NTSC)/7FPS (PAL)
		1.3MP	11FPS (NTSC)/9FPS (PAL)
	General	1MP	15FPS (NTSC)/12FPS (PAL)
		Recording Modes	Schedule, Manual, Motion, Sensor
Playback	Analog Playback Channel	4Ch	
	IP Playback Channels	1Ch	
	Search Mode	Time, Event, File Management	
Backup	USB	1 USB 2.0 Port	
	DVD Burner	Optional	
	Backup Format	AVI/DAT	
Remote Application	Dual Stream	Master Stream 1-25/30FPS@Recording Resolution, Sub-Stream 1-25/30FPS@CIF	
	Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8)	
	Master Stream in Network	Yes	
	CMS	Yes	
	3G	Provision CAM for iOS/Android Phones, Provision HD for iOS/Android Tablets	
	User Access	10 Users Online with Professional Authority Management	
Alarm	Input	No	
	Output	No	
Storage	HDD	1 SATA (4TB)	
	E-SATA	No	
PTZ	Connection	1xRS-485 (IP PTZ Over Network)	
	Supported Protocols	Pelco D, Pelco P, Samsung, Visca, ONVIF	
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus	
Network	Ethernet	100 Mbps (RJ-45)	
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P	
	Dimension	W300xD260xH55mm	
Others	IR Controller	Yes	
	Power Supply	12V/2A	
	Operation Temperature	0°C~50°C	