

16 Channel

CIF/960H

SA-16400NX



Front Panel



Rear Panel



Specifications

MODEL		SA-16400NX
System	Compression Format	Baseline H.264
	OS	Embedded Linux
Video	Input	16CH BNC Connection
	Standard Output	VGA, CVBS
	Advanced Output	HDMI, Spot
Audio	Input	2CH
	Output	1CH
	Two way audio	Yes
Recording	Real-Time Recording	16CH CIF Real-Time
	HD-SDI	No
	960H	120FPS (NTSC)/100FPS (PAL)
	D1	240FPS (NTSC)/200FPS (PAL)
	CIF	480FPS (NTSC)/400FPS (PAL)
Recording Mode		Schedule, Manual, Motion, Sensor
Playback	Playback Channel	16CH
	Search Mode	Time, Event, File Management
Backup	USB	1 USB 2.0 Port
	DVD Burner	No
	Backup Format	AVI/DAT
Remote Application	Dual Stream	Master Stream 1-12/15FPS@D1, Sub-Stream 1-25/30FPS@CIF
	Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8)
	Master Stream in Network	Yes
	CMS	Yes
	3G	ProvisionCAM for iPad/iPhone/Blackberry/Android/Symbian/Windows Mobile
	User Access	18 Users Online with Professional Authority Management
Alarm	Input	No
	Output	No
Storage	HDD	1 SATA (3TB)
	E-SATA	No
PTZ	Connection	1xRS-485
	Supported Protocol	Pelco D, Pelco P, Samsung, Visca
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
Network	Ethernet	100 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
Others	Dimension	W300xD260xH55mm
	IR Controller	Yes
	Power Supply	12V/2A
	Operating Temperature	0°C ~50°C