

# 24/32 Channel

## D1

### SA-32800HD(1U)



Front Panel



Rear Panel



### Specifications

<b>MODEL</b>		SA-32800HD (1U)
<b>System</b>	Compression Format	High Profile H.264
	OS	Embedded Linux
<b>Video</b>	Input	32CH Standard BNC
	Standard Output	VGA, CVBS
	Advanced Output	HDMI, Spot
<b>Audio</b>	Input	4CH
	Output	1CH
	Two way audio	Yes
<b>Recording</b>	Real-Time Recording	32CH D1 Real-Time
	HD-SDI	No
	960H	No
	D1	960FPS (NTSC)/800FPS (PAL)
	CIF	960FPS (NTSC)/800FPS (PAL)
<b>Recording Mode</b>		Schedule, Manual, Motion, Sensor
<b>Playback</b>	Playback Channel	16CH
	Search Mode	Time, Event, File Management
<b>Backup</b>	USB	1 USB 2.0 Port
	DVD Burner	Optional
	Backup Format	AVI/DAT
<b>Remote Application</b>	Dual Stream	Master Stream 1-25/30FPS@D1, Sub-Stream 1-25/30FPS@CIF
	Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8)
	Master Stream in Network	Yes
	CMS	Yes
	3G	ProvisionCAM for iPad/iPhone/Blackberry/Android/Symbian/Windows Mobile
<b>User Access</b>		10 Users Online with Professional Authority Management
<b>Alarm</b>	Input	16
	Output	1
<b>Storage</b>	HDD	2 SATA (3TB)
	E-SATA	No
<b>PTZ</b>	Connection	1xRS-485
	Supported Protocol	Pelco D, Pelco P, Samsung, Visca
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
<b>Network</b>	Ethernet	1000 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
<b>Others</b>	Dimension	W430xD420xH90mm
	IR Controller	Yes
	Power Supply	100-240 VAC
	Operating Temperature	0°C ~50°C