

Advanced telephone alarm dialer capable of remote control via a telephone line.

The dialer sends an alarm message from a supervised facility via a telephone line. It is applied in burglary protection systems, in industrial automation systems and in any other applications requiring automatic transmission of digital or voice messages.



Setup

DIAL09 can be up from a PC computer level via UT1 interface.

D09Load software under DOS and Windows is available.



Software under Windo ws

ony System Monitorowanie Zdatzenia Pomoc 🔁 🔁 💁 🔊 🕿 📀 🖶 🗢 🗢 🔂 🖾 🔚	@[
Opcje systemowe	2
Blokada klawiatury po trzech próbach:	○ NIE
Blokada getekcji i braku napięcia w linii telefoniczne;	C NIE C TAK
Blokada funkcji reprogramowania gegara:	C NIE C TAK
Blokada zapisu <u>k</u> omunikatu alarmowego:	• NIE O TAK
Blokada ponownego programowania instalatora:	C NIE C TAK
§ kolejek telefonowania (notmalnie 4):	C NIE C TAK
Komunikat gransmitowany 4 razy (normalnie 2):	
Funkcja gamouzbrajania:	🖲 NIE I CI TAK



*10 Glowne menu - Fi Podpowiedz - Alt-X Wyjscie z pro

Technical specification

- 15-second alarm message and voice messages on dialer ARMED/DISARMED mode,
- operation with two alarm monitoring stations,
- notification of up to two pager subscribers,
- notification of up to eight telephone subscribers with voice message,
- remote readout of information about the current dialer status,
- remote and local control of programmable outputs,
- remote deletion of alarms,
- set of control codes of different authorizations,
- three universal NO/NC inputs,
- two programmable outputs of 1.0A load capacity,
- built-in capacitive microphone and headphone output,
- capability of operation as a telephone messaging alarm control panel,
- non-volatile EEPROM memory,
- 12VDC power supply,
- ABS casing,
- dimensions: width/height/depth 212x94x36 [mm], weight: 0,28 [kg].



roger 8 82-4 Pola tel./1

ROGER sp.j. Gosciszewo 59 82-416 Gosciszewo Poland tel./fax +48 (055) 272 01 32 +48 (055) 272 34 79 e-mail: roger@roger.pl http://: www.roger.pl

Updated III 2003

Zoom among images can vary. Product specifications and availability is subject to change without notice. Certain product names mentioned herein may be trade names and/or registered trademarks of their companies.