RCP MASTER USERS MANUAL

ver. 1.2.0

Rev. A

TABLE OF CONTENTS

roger

roger

1. INTRODUCTION

1.1. Purpose

RCP Master 1.1. is a software tool for Time and Attendance (T&A) reporting and analysis.

1.2. Modules

The program consists of the following modules:

- ♦ employee data configuration
- ♦ work calendars configuration
- ♦ control point list (T&A readers)
- ♦ T&A event log

1.3. Data storage

Figure 1. *Roger RCP Master datafile*

All application data is stored in a MS Access database file (***.rta** extension). Therefore, the application may open many databases (using the **File**/**Open** command). The **Tools** menu makes the following commands available:

- ♦ data file encryption/decryption (please note that working with an encrypted file can slow the application down by about 15%),
- ♦ setting password for access to data file,
- ♦ data file compacting/repair.

Databases can be accessed programmatically from any IDE (**Integrated Development Environment**) supporting MS Access databases or ODBC (**Open Database Connectivity**) — e.g. Delphi, Visual Studio, Java). By default, the database is password-protected. The default password is „roger".

1.4. Multiuser mode

The application allows for concurrent connections of several operators to one database at a time. To enable such a mode of operation, database should be shared on a networked location, and the operators should be given relevant read/write access rights. The file shared can be opened by the **File**/**Open** command.

1.5. Data export and import

The program allows for manual data input and modification. It is also equipped with the following import/export mechanisms:

- ♦ Import of configuration data and T&A event log from RACS version 4.2.5.38 and higher.

roger

♦ Import of T&A event log from T&A Access Pro file format.

♦ Import/export of configuration data and T&A event log from RCP Master in XML.

♦ Export of all the reports in Adobe Acrobat (**.pdf**), Microsoft Excel (**.xls**), Microsoft Word (**.doc**), Rich Text Format (**.rtf**) and Crystal Reports (**.rpt**) formats.

♦ Additionally export of work time reports in XML.

2. REQUIREMENTS

RCP Master requires installation of the Microsoft .NET Framework 2.0 (available for download on the vendor's site at *http://www.microsoft.com/downloads/details.aspx?displaylang=pl&FamilyID=0856eacb-4362-4b0d-8edd-aab15c5e04f5)*.

The **.NET Framework 2.0** requirements are listed below:

Supported operating systems: Windows 2000 Service Pack 3; Windows 98; Windows 98 Second Edition; Windows ME; Windows Server 2003; Windows Vista Business; Windows Vista Business 64-bit edition; Windows Vista Enterprise; Windows Vista Enterprise 64-bit edition; Windows Vista Home Basic; Windows Vista Home Basic 64-bit edition; Windows Vista Home Premium; Windows Vista Home Premium 64-bit edition; Windows Vista Starter; Windows Vista Ultimate; Windows Vista Ultimate 64-bit edition; Windows XP Service Pack 2

Software requirements:

♦ *Windows Installer 3.0* (except of Windows 98/ME which requires *Windows Installer 2.0* or higher). The *Windows Installer 3.1* or newer is reccommended.

♦ *Internet Explorer 5.01 or higher*: For all the installations of .NET Framework, the Microsoft Internet Explorer 5.01 or higher also must be installed.

♦ In case of Windows Vista the Service Pack 1 must be installed.

Disk space requirements: 280 MB (x86), 610 MB (x64).

3. INSTALLATION AND FIRST USE

To install RCP Master you need to execute the installer (**setup.exe**). When the program is run for the first time after the installation, it displays a question if the sample data from **Demo.rta** should be loaded. If you answer **Yes**, the sample database will be read. Each time a data file gets opened, the application displays a login dialog box as shown in Figure 2:


Figure 2. *Login dialog box*

In the demo file (**Demo.rta**), password for the **ADMIN** operator is empty (no password), so click **OK**.

You can define any number of operators for the specific data file. For all of them you need to configure passwords and set up access rights for performing particular application commands.

4. USE SCENARIOS

4.1. Preparing for work after installation

In order to prepare program for work, it needs to be properly set up. You need to perform the following steps:

1. Create a new data file using **File/New** menu command.

2. Enter data on groups, employees, control points and T&A event types. You can do it manually or import from PR Master (using **Backup.zip** or **Config.xml** files). To import data use **File**/**Import and export** command.

3. Define calendar day types — choose **Calendar day type definitions** command from the **Tools** menu.

4. Define work calendars – choose **View/Calendars** menu command.

5. Assign calendars to employee groups (or individual employees) – choose **Assign calendar to employees** command from the shortcut menu.

6. Finally you can run a command for checking if work calendars have beeen assigned to all the employees — select **Tools**/**Verify data completness**.

4.2. Work time analysis and reporting

One of the typical uses of RCP Master is to generate time an attendance (T&A) reports based on employee T&A event registrations. Correct calculation of working hours requires that complete data of arrivals/departures events is registered. The program is capable of detecting incomplete events (by using the aforementioned **Verify data completness** command). They are indicated in any report by an appropriate warning (red icon with exclamation mark together with a comment). Such missing entries must be completed by the operator manually, i.e. by marking the entry as an absence or manually inserting a missing T&A event (in the **Work history** window).

To generate T&A reports, you should typically perform the following steps:

1. Import T&A events log from file.

2. Use **Verify data completness** command.

3. Send notices to employees, for whom missing/incomplete entries exist in the event log, and ask them for explanation.

4. Correct data manually (by entering an absence or inserting missing events to the T&A events log).

5. Generate reports (you can use wizard for selected employee groups). After generation, the wizard will send to every employee her/his reports using e-mail address configured in employee's data.

5. RCP MASTER FUNCTIONALITY

5.1. Introduction

5.1.1. Home page

By default the program starts with the home page opened (Figure 3). There you can find commonly used application's commands, links to recently opened data files, and links to help files.


Figure 3. *RCP Master home page*

5.1.2. Main window

The main window (displayed after the user logs on and the data file opens — sample is shown in Figure 4) contains the following items:

♦ In the title bar shown at the top of the window there is application name (**RCP Master**), the logged in operator ID enclosed in square brackets, and the active database path in quotes.

♦ Below the title bar you can find the program menu. Its elements have been described in detail in section *Functionality description*.

♦ The toolbar, which is located below the menu, contains shortcuts to the application's most common commands and functions.

♦ The panel on the left side of the window contains a tree with hierarchical structure of the data elements. Each section of the tree is assigned a shortcut menu with commands relevant to the particular item (to show the menu you need to click the item with right

roger

mouse button). When you double-click the item with left mouse button, the window is opened with the document assigned to the item.

♦ On the right hand side of the window there are documents shown as tabs. Some documents are split into two parts. The upper section contains the list, and the lower — the detailed view of the selected list item. The windows contain buttons for invoking commands.

♦ In the bottom of the main window there is application's status bar containing information about operations being performed as well as a progress bar.

Figure 4. *RCP Master's window layout*

5.1.3. Reporting errors

RCP Master features error reporting mechanism. In case of unexpected error, the program displays window similar to the one shown in Figure 5. It contains necessary information relevant to the context and the source of the error. To send an error report you need to click **Send report** button. The program invokes then a MS Outlook window containing e-mail with error report. The only thing you need to do is to click the **Send** button in Outlook.

roger

Figure 5. *Unexpected error*

5.2. Functionality description

5.2.1. File menu

The **File** menu is shown in Figure 6.

Figure 6. *The File menu*

5.2.1.1. New

Creates a new data file and opens it.

5.2.1.2. Open

Opens an existing ***.rta** data file*.*

5.2.1.3. Save as

Saves currently opened data file in the file under different name.

5.2.1.4. Close

Closes all the editing windows of the current data file and displays the home page of the program.

5.2.1.5. Import and export

Opens the data import/export wizard. When the user has selected **Import T&A event registration from another software** action, the wizard performs the following steps (shown in figures 7–9 below):

♦ Step 1. Select T&A data import/export action (Figure 7).

Figure 7. *Data import and export wizard — step 1*

♦ Step 2. Select data file format (when importing data from PR Master — Figure 8).

♦ Step 3. Select location to your T&A event file (Figure 9). Using available options you can choose a method of resolving conflicts in case, the imported value is already in database. If you choose **Replace duplicates with imported items**, duplicate values existing in the database will be overwritten by the imported values. The **Do not import duplicates** option skips duplicated records. Two T&A events are assumed equal, if their date/time, reader ID and event type are identical.

roger

Figure 8. *Data import and export wizard — step 2*

Figure 9. *Data import and export wizard — step 3*

5.2.1.6. Recent documents

Shows a list of recently opened data files. Clicking an item on the list opens the selected document.

5.2.1.7. Exit

Closes the active datafile and exits the application.

## 5.2.2. View menu

The **View** menu is shown in Figure 10.

Figure 10. *The View menu*

5.2.2.1. Employee groups

Opens the **Employee groups** window. As mentioned above, the document window is composed of two parts — the upper section is usually a list (e.g. a list of employee groups), and the lower — the detail section, where information related to selected list item is shown (in Figure 11 it is the group **Administration**). The detail pane can be closed at any time by clicking the cross icon on blue background located in the right side of detail pane's title bar. To reopen it, click the **Show details** button on the right side of the upper pane.

Figure 11. *Employee groups window*

roger

Items on the list can be added, edited or removed. In addition, there can also be other commands on the toolbar, such as **Refresh**, **Create report**, and so on. They can be different depending on the particular window selected. Clicking the **Edit** button spowoduje pojawienie się okna edycji umożliwiającego wprowadzenie opisujących daną grupę pracowników informacji. Po wypełnieniu poszczególnych pól należy wcisnąć przycisk **OK** jeśli chcemy dokonać zapisu wprowadzonych danych bądź **Anuluj** jeśli chcemy zrezygnować z edycji (rysunek 12).

(Figure 12).

Figure 12. *Edit employee group dialog box*

Required fields in edit windows are marked in yellow (in this case the **Name** field is required).

5.2.2.2. Employees

Opens the **Employees** window (Figure 13).

Figure 13. *The Employees window*

roger

The detail section of the employee window contains four tabs:

Details

The **Details** tab contains the following data about employee (Figure 14):

- ♦ **Photo** — employee's picture (automatically resized to save space in the database). Pictures (as any other data) are stored in the currently opened datafile.

- ♦ **T&A ID** — employee's unique ID. An employer is identified in the program using this unique identifier. Thanks to this, there can be employees of the same first name and last name in the database, Moreover, changing names has no influence on the proper employee's identification.

- ♦ **First name** and **Last name**.

- ♦ **Group** — indicates the employee group, the employee belongs to. Grouping accelerates calendar assignments, reporting, etc.

- ♦ **Calendar** — used for employee work schedule assignment. T&A calculations are based on calendar contents as well as a T&A event log.

- ♦ **Hire date** and **Dismissal date** — (optional fields) are used to determine a time interval for T&A calculations for the particular employee. For example, if you create a report for an employee, who was dismissed in mid January, you should enter a dismissal date as well. Otherwise the program will report missing entries in the event log.

- ♦ **E-mail** — the field contains an e-mail address, which will be used to deliver generated reports (as attachements in PDF format).

- ♦ **Comments** — additional data.

**Figure 14**. *The Details tab of the Employees window*

Clicking the **Edit** button displays the **Edit employee** dialog box (Figure 15), where you can modify employee's data. Required fields are highlighted in yellow. Red icon with an exclamation mark shown on the right of the **Calendar** field indicates that employee's data is invalid. When you move the mouse cursor over the icon, the message is displayed that the calendar has not been assigned to the employee. Such red icon accompanied with appropriate comment indicate invalid data also in other editing windows.

roger

Figure 15. *Edit employee dialog box*

Work history

Zawiera wynik obliczeń czasów przebywania danego pracownika w określonym przedziale czasu. Contains results of T&A calculations regarding time spent at work in the period selected. In the pane's title bar the calendar's name is shown. Next to it there is **Time range** dropdown list. The list contains month names, and in the bottom there is the **Select time range…** command. Clicking the month name causes recalculation for the month selected. When you select the **Select time range…** command (Figure 16), you will be presented with the dialog box, where you can more accurately determine calculation period (up to minutes):

Figure 16. *The Select time range... dialog box*

The **Work history** window is composed of two basic views — **Attendance** (the calculation results), and the **Event log** (the filtered list with events pertaining to the employee in the selected

time range. The calculation result of attendance data for the employee can be shown in various preview modes (by clicking **View** commands on the toolbar).

View: List of days

The most generic view of hours spent at work in the form: list of days — total time, time to be accounted for (Figure 17). On the right side of the window, the calendar is displayed showing days in colors representing particular day and absence types. In the bottom of the window the calculation results summary is displayed (remaining hours to work, the total time to be accounted for, the balance, as well as information regarding night hours, overtime, sundays, holidays, and so forth).

View: Calendar day details

It contains all the information included in the **List of days** view. Additionally, each day has been analyzed in detail. Attendance periods are shown chronologically using calendar day and T&A event definitions. So, it includes compulsory breaks, work time, overtime, and so forth. Late arrivals, early departures, and other discrepancies to the work schedule (work regulations) are indicated in the list by the warning yellow icon accompanied with the relevant comment (early departure, late arrival, etc.). The same icon is shown on the calendar in the right side of the window (see Figure 18). If you click a date on the calendar, the list is scrolled to the day selected.

View: Total time

It contains all the information included in the **List of days** view. In addition for each day, the total time for the specific attendance types are shown: such as total time of cigarette breaks, other type of breaks, work time, hours outside the office, and so on (Figure 19).

View: Discrepancies

In this view, all the discrepancies to the employee's work schedule (work regulation) are shown (late arrivals, early departures, exceeded break limits — e.g. cigarette breaks, and so on). In the example shown in Figure 20 it is for instance the early departure logged on January, the 24th. This view is most often used for employee's work analysis and for correction missing log entries. Events can be inserted using the **Add** command in the toolbar. You can also edit absence by the **Edit absence** command shown above the calendar, on the right side of the window.


**Figure 17**. *The List of days view*

roger

Figure 18. *The Calendar day details view*

Figure 19. *The Total time view*

Figure 20. *The Discrepancies view*

Leave entitlements

According to the labour code, employees are entitled to paid or unpaid leaves. In the **Leave entitlements** tab (Figure 21), you can enter values describing yearly leave limits for the particular types (leave types can be defined using **Tools**/**T&A type definitions** command). In addition, in this window the number of days for the specific leave type and the remaining number of days are displayed.

Figure 21. *Leave entitlements tab*

Work calendar

All the employees have work calendars assigned to them (Figure 22). However, from time to time, it is necessary to modify work calendar of particular employee. It can be caused by, for example, replacements done between employees, compensation for past or future absences, and so on.

roger

Figure 22. *Selected employee's work calendar*

To modify the calendar assigned to the employee, you need to click the **Correct employee calendar days** button. Days modified in the calendar are marked by a border (note the 16th and 18th January in Figure 22 above). To display original or(and) modified calendar days, you need to select appropriate option in the **View** menu). The modified calendar days replace the original ones. In Figure 22, to the 16th January the „Day off" status, and to the 18 January, the „Working day 14:00-22:00" status have been assigned. The modifications apply for the selected employee only.

Reports

In the example presented above, the results of work history calculations have been presented using different views. The program allows for generating reports from any type of view. Reports can be generated by the **Create report** command from the particular window (the printer icon) or, in case of more complicated reports, using a report wizard. Commands for creating reports can be invoked from many locations, e.g. from the navigation tree, group window, employee's detail pane. Using the wizard, you can generate summary reports (for selected employee groups or for all the employees) as well as for individual employees. These reports can be automatically sent as attachements in PDF format using e-mail addresses set up in the employee's data window. Below you can find successive report generation steps for the individual employee (to invoke the wizard, you need to click **Report** command in the employee's detail pane — the first tab — or in the navigation tree, from the shortcut menu of the selected employee — the **Report wizard...** command).

Step 1. Select report types to generate. In the example below (see Figure 23), the generic report on work time, the report on discrepancies to work regulations (late arrivals, exceeded break limits — e.g. cigarette breaks, and so on), the leave entitlements report (the current state of the leave usage) and the work calendar report, have been selected.

roger

Figure 23. *Selecting report types to be generated*

Step 2. Choose period, for which the reports selected are to be prepared (Figure 24).


Figure 24. *Selecting time range for generating selected reports*

Step 3. Select destination directory for PDF files containing reports generated (Figure 25). In addition, you can select option for sending reports to employees as e-mail attachements.

roger

Figure 25. *Selecting destination directory for generating reports*

Step 4. Displaying a progress window for the process of generating reports (Figure 26). After generation, the summary message is displayed.


Figure 26. *Report generation progress window*

Apart from reports generated as PDF files using report wizard (most often for list of elements such as calendars, readers, employees, groups, and so on) there are reports which are displayed as documents. In Figure 27 you can find sample report **List of employees** (invoked by the **Reports/Report "employees"** menu item).

roger

Figure 27. *Report "Employees" displayed in document window*

The report is ordered by the employee group name (displayed on the left side of the window). When you click specific group name, the report will be scrolled to the location, where the data of the selected group begins. Reports can be printed and exported in many different formats such as: Crystal reports (**.rpt**), Adobe Aprobat (**.pdf**), Microsoft Excel (**.xls**), Microsoft Word (**.doc**), Rich Text Format (**.rtf**).

5.2.2.3. Calendars

Opens the **Calendars** window (Figure 28). On the right side of the window, the legend is displayed explaining colors representing particular day types on the calendar.

Figure 28. *The Calendars window*

roger

Clicking the **Edit calendar days** button displays the **Edit calendar days** dialog box (Figure 29), where you can modify the calendar. On the right side of the window, there is a legend with day types, which can be assigned to the calendar. Assignment is done by selecting days with left mouse button. Then you need to click right mouse button and select the day type from the shortcut menu. To remove an assignment, you need to select apropriate days on the calendar, and choose the **Remove assingnment** command from the shortcut menu. At the top of the window there is **Insert holiday** menu. When you expand it, you can select predefined public holidays for inserting into the calendar.


Figure 29. *Edit calendar days dialog box*

In order to make selecting days within the whole year easier — for instance by some rule (e.g. all the Mondays, Wednesdays and Fridays in June and August), you can use the command **Select days by rule** which can be invoked at the top of the window or from the context menu (Figure 30).


Figure 30. *Selecting days by rule*

roger

5.2.2.4. Control points

Opens the **Control points** window (Figure 31).

Figure 31. *The Control points window*

Clicking the **Edit** button displays the **Edit control point** dialog box (Figure 32), where you can modify the control point. **T&A Point ID** determines an unique control point's ID. Thanks to this ID, the change of the control point name will not influence the calculation results. **T&A Point ID** is an arbitrary string. By default, when configuration is imported from PR Master, it gets the following values: **subsystem ID**/**controller ID**/**reader ID**.

Figure 32. *The Edit control point dialog box*

5.2.2.5. T&A event log

Opens the **T&A event log** window (Figure 33). In the top section of the window there is an event list displayed in chronological order. By selecting dates **Interval from:** and **To:** in the upper section of the window you can narrow down the time interval. In the details pane all information relevant to the event is displayed, i.e: employee's T&A ID, first and last names, pictures (where assigned), group, time, control point and T&A event type. Apart from these, there are two flags determining if the events were edited in any case (added, modified or removed). There is also an

roger

indication if the event has been removed by an operator (such an event is grayed out and understriked in the list).

Figure 33. *T&A event log window*

Clicking the **Edit** button displays the **Edit T&A event** dialog box (Figure 34), where you can modify T&A event's data.

Figure 34. *Edit T&A event dialog box*

5.2.2.6. Home page

Opens the **Home page** containing three groups of commands.

The **Common tasks** group (Figure 35) contains shortcuts for most commonly used program's commands:

- ♦ **Open data file…** – opens dialog box for selecting **.rta** data file.
- ♦ **Create new data file…** – opens dialog box for saving a newly created data file.
- ♦ **Import T&A events** — opens T&A data import wizard.

♦ **Verify data completness...** — invokes function for checking data completness (assignment of calendars for all the employees, completness of arrivals and departures registration) and displays results in the pane at the bottom of the main window.

♦ **Find discrepancies against work regulation...** — invokes function for checking discrepancies against the work regulation (late arrivals, early departures, missing log entries, exceeded minimum or maximum time limits) and displays results in the pane at the bottom of the main window.

♦ **Employee report wizard** — opens report wizard window for all the employees.

♦ **Find employee...** — opens the **Find employee** dialog box (Figure 36).

Figure 35. *Common tasks area on the home page*

Figure 36. *Finding employee dialog box*

If you enter the employee's name (full or part) or the T&A ID, the program finds the employee in the navigation tree, expands the group branch, the employee belongs to, selects the employee's branch and opens the employee's document window.

The **Recently opened** group (Figure 37) contains paths for recently opened data files (***.rta**): Clicking the path will display a logon window and load data from the file selected.

Figure 37. *Area Recently opened on the home page*

roger

The **Help** group (Figure 38) contains commands for displaying program documentation and for getting help:

♦ **Function description** — opens document window with program's function description.

♦ **FAQ** — opens document window with program functionality description in the form of questions and answers.

♦ **Troubleshooting** — opens document window with problems description together with its solutions.

♦ **Open example (demo) file...** — loads sample data file (configuration and T&A events of fictitious company) for testing program;s functionality.


Figure 38. *Area Help on the home page*

5.2.2.7. Navigation tree

Opens **Navigation tree** window (Figure 39) representing data as a hierarchical tree. The main branches of the tree are the main RCP Master modules, namely: employee groups with employees, work calendars, control points, and T&A event log. To quickly find an element of particular name in the tree, you need to type the name (or its part) in the **Find** field (at the top of the window), and press **Enter**, or click **Search** button located on the right side of the field (to find next occurences of the name in the tree, you need to click the **Search** button as many times as the name is found). Moving from element to element in the tree can be done using mouse or the keyboard (arrow keys). Pressing **Enter** or double clicking the element in the tree opens the document assigned to this element (i.e. clicking employee name opens employee's document window).

Figure 39. *Navigation tree*

To display command list associated with the particular tree element, you need to right click it — the context (shortcut) menu will be displayed (Figure 40).

roger

Figure 40. *Shortcut menu associated with selected tree element*

By clicking the selected menu item, we invoke the command for the element selected (e.g. you can assign the calendar to employee using **Assign calendar to employees** command — Figure 41).


Figure 41. *Assigning calendar to employee from the shortcut menu*

5.2.2.8. Previous/Next document

If more than one document is opened at a time, then commands **Previous** and **Next** allow for moving between them in the same order as they were opened.

roger

5.2.3. Tools menu

The **Tools** menu is shown in Figure 42.

Figure 42. *The Tools menu*

The commands of the **Tools** menu have been described in the following sections.

5.2.3.1. T&A event type definitions

Opens the **T&A event type definitions** window (Figure 43). The T&A event type determines how the event logged by the control point will be interpretted, for example: arrival, departure, going out on business. The event type is uniquely identified by the numerical code. You can define any number of T&A event type definitions


Figure 43. *T&A event definition window*

Clicking the **Edit** button displays the **Edit event type** dialog box (Figure 44), where you can modify the particular event type.


Figure 44. *Edit event type dialog box*

5.2.3.2. T&A type definitions

Opens the **T&A type definitions** window (Figure 45). T&A type is used to determine attendance type of the employee in the particular time. Sample attendance types are as follows: **Work**, **Going out on business**, **Breakfast**, **Overtime**, **On vacation**, **Sick leave**, and so on. You can define any number of attendance types.

The **Details** pane contains the following data about attendance type:

♦ **Code** — unique code identifying attendance type.

♦ **Name** — textual name.

♦ **Color** — color displayed in the calendar.

♦ **Time period** — it can get two values: **Interval** (it means, that the attendance type determines time interval up to minutes — e.g. work, breakfast break, cigarette break, overtime, etc.) or **Day** (indicates that the attendance type applies to the whole working day e.g. vacation, sick leave, business trip, etc.).

♦ **Start** — (optional) determines the event type which start counting time for the particular attendance type (e.g. the event — **Arrival** can begin the attendance type **Work**; the event **Going out on business** can start the attendance type **Out on business**).

♦ **Included into working hours** — determines if the particular attendance type will be included into working hours (e.g. breakfast break is included into working hours whereas lunch break is not included; sick leave is included, but unpaid leave is not, and so forth).

♦ **Leave** — determines if the particular attendance type indicates leave — i.e. it is shown in the **Leave entitlements** window for the particular employee.

♦ **Comments** — additional info.

roger

Figure 45. *T&A type definitions window*

Clicking **Edit** button displays the **Edit attendance type** dialog box (Figure 46), where you can modify the selected attendance type.


Figure 46. *Edit attendance type dialog box*

roger

5.2.3.3. Calendar day type definitions

Opens the **Calendar day type definitions** window (Figure 47). Calendar day type is a pattern (schedule) of work in the particular day — e.g. workday from 8:00AM to 5:00PM with a lunch break (unpaid) from 1200PM to 1:00PM. Calendar day types, as the name suggests, are used for work calendar definitions. Work calendar creation is the process of assigning day types to selected days in the calendar — e.g. for all days from Monday to Friday the type: Workday 08:00AM-04:00PM can be assigned. More about calendars can be found in the *Calendars* section.

Figure 47. *Calendar day type definition window*

Clicking the **Edit** button displays the **Edit calendar day type** dialog box, where you can modify the selected calendar day type (Figure 48). The day type definition consists of the following fields:

- ♦ **Code** — unique code identifying day type.

- ♦ **Name** — unique name of day type.

- ♦ **Color in calendar** — color for representing the type of day assigned to the calendar.

- ♦ **Comments** — additional info.

- ♦ **Type** — it can get the following values: **Working** (indicates compulsory attendance at work); **Extra working** (means extra working day which is not compulsory); **Holiday** (means a public holiday); **Day off** (free day not counted in the calculations).

roger

♦ **Hours** — it can get two values determining the way of work: **Fixed** (work from defined time to defined time); **Flexible working hours** (work type, where the start and the end of the workday is not set; it is possible to define daily hours limit and the time of start/end the workday — e.g. for accounting the flexible working hours during the night shift).

Figure 48. *Edit calendar day type dialog box*

In addition, the day definition may contain configuration items which will be shown after clicking the **Show details** button (Figure 49). Additional options are divided into the following tabs:

Options tab contains several options related to work time calculation, and showing information related to the work regulation (schedule):

♦ **Include early stay at work...** — you can define the point of time (before the usual working hours), from when the early stay at work will be included into working hours.

♦ **Include late stay at work...** — you can define the point of time (after the normal working hours), until when the late stay at work will be included into working hours.

♦ **Mark as late arrival...** — you can define the point of time, from when the employee's arrival will be counted as late coming.

♦ **Mark as early departure...** — you can define the point of time, before when the employee's departure will be counted as early.

♦ **Night hours** — indicates the range which will be counted as night hours.

roger

Figure 49. *Work time calculation parameters — details*

Regulatory breaks

Allows for definition of regulatory breaks, e.g. breakfast break (Figure 50). The program will automatically count the work time within the range defined as the type indicated in the breaks list.

Figure 50. *Regulatory breaks tab*

Overtime

Allows for definition the overtime in the particular day (Figures 51 and 52). The program will automatically count the work time as overtime according to the rules defined. There are two methods of overtime counting:

Fixed hours: defined by selecting the hours range **From**-**To**. The **Attendance type** column determines the overtime type accounted for in the particular time range (e.g. **Overtime 1** – 50%, **Overtime 2** – **100%** and so on)**.**

roger

Figure 51. *Overtime definition tab*

Variable hours: calculated dynamically (after the specific number of hours has been worked through). Defined by indicating the number of hours worked through after which the system should start counting the specific overtime type. For example: in the first row of the Figure below, there is information that the overtime should be counted after 8 hours of work — e.g. if an employee worked from 7:00 am to 4:00 pm, then the "Overtime 1" period starts at 3:00 pm.

Figure 52. *Overtime tab — variable hours*

Additionally, the column **If an employee has worked at least for** allows for defining even the most complicated overtime definition.

For example: we are supposed to define overtime in such a way that after 8 hours of work, the overtime 50 % be counted (i.e., for example, **Overtime 1**). Additionally, if an employee worked longer than two overtime hours (i.e more than 10 hours in total), then 100 % overtime should be accounted for (i.e., for instance, **Overtime 2**) from the beginning of overtime period, so after 8 working hours. The method of defining this kind of overtime has been described below.

Definition example: In the window above, two overtime types have been defined. Both begin after 8 hours of work. As an additional condition there is a statement, that the first overtime period should start after an employee worked at least for 8 hours, the second after she/he worked at least for 10 hours. In Figure below there is work history for an employee who worked form 7:00 am to 4:50 pm. As you can see, the employee worked more than 8 hours, so the "Overtime 1" type were accounted for.

roger

Start	Attendance type	Event	Control point	Comment	Total time	Time to be accounted for	Edited
1/2/2008	**Working day 7-15**			**TOTAL:**	**9:50**	**9:50**	☐
7:00 AM	Work	T&A - Entry	Office building - ENTRY		8:00	**8:00**	☐
3:00 PM	Overtime 1				1:50	**1:50**	☐
4:50 PM	Outside work	T&A - Leave	Office building - EXIT				☑

On the other hand, if an employee worked more than 10 hours (e.g. from 7:00 am to 5:40 pm), then the "Overtime 2" type should be accounted for him. This is according to the setting in the If an employee has worked at least for column.

Start	Attendance type	Event	Control point	Comment	Total time	Time to be accounted for	Edited
1/2/2008	**Working day 7-15**			**TOTAL:**	**10:40**	**10:40**	☐
7:00 AM	Work	T&A - Entry	Office building - ENTRY		8:00	**8:00**	☐
3:00 PM	Overtime 2				2:40	**2:40**	☐
5:40 PM	Outside work	T&A - Leave	Office building - EXIT				☑

Rounding

Allows for definition of roundings for the start and end of work times. In the sample shown in Figure 52, the counting of the start has been set every 30 minutes, and the allowed time margin — 5 min. It means, that the employee's arrival, e.g. at 7:50AM or 8:04AM will be rounded to 8:00AM, but the arrival, e.g. at. 8:08AM will be rounded to 8:30AM. The options set for the end of work have the following meaning: if departure took place at 3:55PM, it will be rounded to 3:45PM, but departure at 3:59PM or 4:08PM will be rounded fo 4:00PM. Times rounded are visible in the employee's work history with a tilde mark — e.g. `~ 8:00`.

Figure 52. *Rounding definition tab*

Hours at work

Allows for definition of constraints list for times spent within the particular attendance types (see Figure 53). For example, we can define maximum total cigarette break time, lunch breaks time or define minimal expected work time hours.

roger

Figure 53. *Hours at work tab*

5.2.3.4. Program operators

Opens the **Program operators** window (Figure 54). In the top section of the window there is operator list. The bottom section displays rights to execute particular program's command defined for the selected operator.


Figure 54. *The Program operators window*

Clicking the **Edit** button displays the **Edit operator data** dialog box (Figure 55). You can change there the operator's password, and select program's commands available for her(him). In order to do this you need to select relevant checkboxes in the program commands tree.

roger

Figure 55. *Editing operator data*

5.2.3.5. Operator action history

Opens the **Operation history by operators** window (Figure 56). In this window you can track operator's activities and commands which they invoked from the time they logged on, until the moment of ending work with the application. The history contains also errors logged during application's activity. The operation history can be saved in **.csv** format (comma separated text file) using the **Save as…** command.

roger

Figure 56. *Operator action history window*

5.2.3.6. Verify data completnes

Invokes function for checking data completeness (i.e. assignment calendars for all the employees; completness of arrivals and departures registration) and displays results in the pane at the bottom of the main window. In the results window (Figure 57) you can click the **Edit** button and correct data selected in the list.

Figure 57. *Results of data completness check*

5.2.3.7. Find work regulation discrepancies

Invokes function for checking discrepancies against the work regulation (late arrivals, early departures, missing log entries, exceeded minimum or maximum time limits) and displays results in the pane at the bottom of the main window (Figure 58). When you double-click data selected in the list in the result window, the employee's document window is opened showing the discrepancies details.

Figure 58. *Discrepancy list pane*

5.2.3.8. Data file menu

5.2.3.8.1. Change file access password

Displays password change window (Figure 59), where you can change password for the current data file. The default password for newly created file is „roger".


Figure 59. *Change file access password dialog box*

5.2.3.8.2. Encrypt file

Displays a dialog box containing a question about encrypting or decrypting file. If you confirm, the action selected will be performed.

5.2.3.8.3. Compact/repair file

Displays a dialog box containing a question about compacting and repairing file. If you confirm, the action selected will be performed.

5.2.3.9. Language

Opens the **RCP Master language selection** window (Figure 60). The drop-down list contains all the languages available for the program. After you select language, all the opened windows will be translated, without closing them.

roger

Figure 60. *RCP Master language selection dialog box*

5.2.3.10. Change license

Displays a dialog box containing a question about removing the current license. If you confirm, the current license is removed, and the program restarts in order to provide a new license in the start window. The command is used e.g. for moving from one-user to multiuser license.

5.2.3.11. Options

Displays the **Options** window (Figure 61). The **Mail settings** tab is used for configuring mail account for sending e-mail reports to employees.

**Figure 61**. *Options dialog box*

The **T&A event import** tab (Figure 62) allows for configuration of quick event import from given location after the operator logs on.

roger

Figure 62. *T&A event import tab*

5.2.4. Help menu

The **Help** menu is presented in Figure 63.


Figure 63. *Help menu*

5.2.4.1. About

Displays dialog box with information about the program version.

roger

5.2.4.2. Program function description

Opens the RCP Master User Manual (PDF) in a built-in document view window. Acrobat Reader is required for this functionality.

5.2.4.3. FAQ

Opens document window with program functionality description in the form of questions and answers.

5.2.4.4. Troubleshooting

Opens document window with problems description together with its solutions.

5.2.4.5. Release history

Opens a document window with RCP Master release notes.

5.2.4.6. Roger home page

Displays the Roger Web site using the RCP Master's dokument window.

5.2.4.7. Send feedback

Opens default e-mail client with the vendor's e-mail address and the subject, allowing for sending feedback to the vendor.

5.2.4.8. Check for updates

Establishes connection with update server in order to check, if newer program version is available for download.

roger

6. GLOSSARY

♦ **Time and Attendance** — set of technical and information technology media for attendance control (presence/absence) during working hours (see also: (*http://en.wikipedia.org/wiki/Time_and_attendance*).

♦ **Control point** – a device for employee identification purposes using PIN codes readers, code cards, proximity crds, biometric methods (fingerprints), etc.

♦ **T&A event log** — a list of events registered by control points.

♦ **Data file compacting** — deleting records in databases is performed by setting a flag indicating that the particular record is deleted, not by physically removing the record (physical removing records is very time-consuming operation). In order to delete records physically, you need to invoke **Tools**/**Data file**/**Compact/repair file** command. Compacting is performed mainly for lowering the size of data file.

♦ **T&A event type** — determines how the event logged by the control point will be interpretted, for example: arrival, departure, going out on business. The event type is uniquely identified by the numerical code.

♦ **T&A type** — used to determine the attendance type of the employee in a particular time range. Sample attendance types are: **Work**, **Going out on business**, **Breakfast**, **Overtime**, **On vacation**, **Sick leave**, and so on.

♦ **Calendar day type** — a pattern (schedule) of work in the particular day — e.g. workday from 8:00AM to 5:00PM with a lunch break (unpaid) from 1200PM to 1:00PM.

roger