

## XD-2L BR

## MULTIPURPOSE DETECTOR

The XD-2L is a multipurpose wired detector, which can operate with any alarm control panel. The device can work as: magnetic contact, shock detector, shock detector and magnetic contact, and water flood detector.

The detector is available in white (XD–2L), brown (XD–2L BR) and dark grey (XD–2L DG).

- option to select detector type with DIP switches
- · modes of operation:
  - o magnetic contact
    - detection of opening of a door, window, etc.
    - input for connecting an NC-type wired detector (e.g. other magnetic contact)
    - 1 alarm output
  - o shock detector
    - detection of shocks and vibrations accompanying attempts to force a door or window, etc.
    - input for connecting an NC-type wired detector (e.g. other magnetic contact)
    - 1 alarm output
  - shock detector and magnetic contact
    - detection of shocks and vibrations accompanying attempts to force a door or window
    - detection of opening of a door, window, etc.
    - input for connecting an NC-type wired detector (e.g. other magnetic contact)
    - 1 or 2 alarm output(s)
  - water flood detector
    - detection of flooding in rooms with plumbing
    - input for connecting external flood probe FPX-1 (white), FPX-1 BR (brown) or FPX-1 DG (dark grey) the probe available separately
    - 1 alarm output
- $\bullet\,$  option to select alarm output type (2EOL/NC or NC)
- $\bullet\,$  option to select EOL resistors for 2EOL configuration
  - $\circ\,$  alarm: 1.1 k $\Omega$  / 2.2 k $\Omega$  / 4.7 k $\Omega$  / 5.6 k $\Omega$  / 6.8 k $\Omega$
  - $\circ$  tamper: 1.1 k $\Omega$  / 2.2 k $\Omega$  / 4.7 k $\Omega$  / 5.6 k $\Omega$
- LED indicator
- remote enabling/disabling of the LED indicator
- supply voltage control
- tamper protection against enclosure opening
- 2 magnets included (for surface and flush mounting)

