

Device

1 Setting 2 Protect 3 OK

Username: admin

New Password:

Weak Middle Strong

Confirm:

Use a password that has 8 to 32 characters, it can be a combination of letters, numbers and symbols (please do not use special symbols like ^, ", \, ~, &)

Next

1 Login to the web interface of the Dahua video intercom.

Device

1 Setting 2 Protect 3 OK

Device Succeed!

OK

The system displays the “Setting” interface if it is the first time you have logged in.
Follow the prompt to set a new password, and save it.

IP VDP Door Station

Web Server V1.0

admin

Forgot Password?

Login

IP VDP Door Station Web Server V1.0

System Config

- > Local Config
- > LAN Config
- > Indoor Manager
- > Network Config
- > Video Set
- > User Manager
- > IPC Information
- > UPnP Config
- > Info Search
- > Status Statistics
- > Logout

TCP/IP FTP Port DDNS P2P

IP Address: 192.168.138.203

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.138.1

MAC Address: 4c:11:bf:7c:d3:34

DNS Address: 8.8.8.8

Default Refresh OK

2 Configure the video intercom network settings.
The IP address must be in the same subnet as the INT-TSI keypad.

System Config

- Local Config
- LAN Config**
- Indoor Manager
- Network Config
- Video Set
- User Manager
- IPC Information
- UPnP Config
- Info Search
- Status Statistics
- Logout

LAN Config

Building No. 01

Building Unit No. 1

VTO No. 6901

Max Extension Index 5 ☒ Group Call

MGT Centre IP Address 10.22.5.254 ☐ Register to the MGT Centre

MGT Port No. 12801

Call VTS Time 00:00 To 23:59 ☐ Call VTS Or Not

NoAnswer Transfer MGT ☐ Enable ☒ Disable

Centre

Warning: The device needs reboot after modifying the config above.
If extensionCount changed, need reboot VTH and init VTH information again!

Default Refresh OK

IP VDP Door Station Web Server V1.0

System Config

- Local Config
- LAN Config
- Indoor Manager**
- Network Config
- Video Set
- User Manager
- IPC Information
- UPnP Config
- Info Search
- Status Statistics
- Logout

Digital Indoor Station Manager

FamilyName	FirstName	Nick Name	Room No.	IP Address	Card No.	Info	Modify	Delete
<div> Add Export Config Import Config </div>								

1 / 1 Go to 10

3 Set the VTO No. of the video intercom (the factory default setting is 6901).

4 In the 'Indoor Manager' settings tab, add the connection between the video intercom and SATEL keypad.

Export Config Import Config

Add

FamilyName

FirstName

Nick Name

VTH Short No.

IP Address

OK Cancel

Warning: The existent vth will be deleted when a new vth added since the device is villa station.

5 Enter the name, VTO No. and IP address of the SATEL keypad. (the factory default VTO No. of the INT-TSI keypad is 9901).

Export Config Import Config

Add

FamilyName TSI

FirstName TSI

Nick Name 9901



VTH Short No. 9901

IP Address 192.168.138.132

OK Cancel


Warning: The existent vth will be deleted when a new vth added since the device is villa station.

6 Set the number (VTO No.) of the video intercom (Factory default is: 6901).




7 A correctly added INT-TSI keypad in the Dahua interface.





8 Configure the second video intercom network settings.



9 Set the VTO No. of the second video intercom.




10 In the 'Indoor Manager' settings tab, add the connection between the second video intercom and the SATEL keypad using the same settings as the first intercom.




11

Run TSI Builder and open the project.




12

Add a new tab.




13

Add the "intercom" widget.




14

Open the "intercom" widget properties.




15

Click the add button (icon: "+").



16

Enter the intercom settings: name, IP address, login, password (the factory default VTO No. is 6901).




17

Enter the intercom settings: name, IP address, login, password (the factory default VTO No. is 6901)





18

Add the "intercom" widget again for the second video intercom.





19





Add the "intercom" widget again for the second video intercom.



20

Enter the intercom settings for the second video intercom






21

Check the assigned number to the INT-TSI keypad in the TSI Builder widget properties.
Caution! The room number is unique, if you have more than one INT-TSI keypad in the system then each keypad must have a different room number.


22

Build the project.



23

Synchronise project with the SD card.



24

After correct synchronisation, insert SD card to the keypad.