ΣΕΔSY Two-wire Video Intercom System



Why '2' Easy?

Characters of 2-easy system

All in One

Power, audio, and video are transmitted by a 2-wire cable

Non Polarity

Never afraid of electric shock

Functional Module on bus wiring

Relay actuator, Camera interface, Memory and call divert module

Central power supply

No ugly pigtail with extra local power supply

Max. 256 users

Audio-







What's New



DX Door stations with Internet connectivity

Video memory _ IP camera connection _ Call divert _ 4G module

XD-Device APP Configuration & Management tool



DX new Wi-Fi monitors

HD Screen_Video memory _ Camera surveillance _ Call divert




Others

DX450 5" Wi-Fi Monitor _ Glass panel

DJ9A hand free phone PMMA

System Door Stations

Metal case _1~32 button call _ Keypad _Modularized



System Indoor Monitors

4.3 " _ 7 " _ Touch screen _ Memory record _ Call divert

Basic Monitor 4.3" & 7"









OSD _ icon menu _ Handset add on'

Wi-Fi Monitor 5" & 7"










Wi-Fi connectivity Call divert HD TFT video memory IPC connection PIP Quad

^{*} For certain models

System Accessories

Simple & Intelligent Isolation protection Bus connection



Both can be used as the 2nd lock controller or stair light controller

^{*}Full name: 2S---DBC2S, 4A---DBC4A1, 4R---DBC4R, RLC*—Mini-RLC

System Capacity

Capacity in villa and apartment system

Basic Villa








Can be extended 3 monitors in one apartment DX821 only supports one door station as an exception

Max.4 outdoor stations, 32 Indoor monitors in apartment system Have ability to be extended to 256 monitors by BDU router function

Typical Wiring In-out Topology

Hand-in-hand Wiring, without distributor





Cable	Α	В
Twisted 2x0.75mm	60	100
Twisted 2x1.00mm	80	120
Cat5(Combine)	40	80

^{*}Distance based on monitor quantity less than 2pcs

Typical Wiring Star Topology

Star Wiring via DBC2S or DBC4A or DBC4R Distributor






Cable	A	В
Twisted 2x0.75mm	60	40
Twisted 2x1.00mm	80	60
Cat5(Combine)	-	-


^{*}monitor quantity less than 16pcs

Typical Apartment Wiring

Monitors connection via DBC4 Branch distributor








Cable	Α	В	С	
Twisted 2x0.75mm	60	60	30	
Twisted 2x1.00mm	80	80	40	
Cat5(Combine)	50	50	20	

*monitor maximum 32pcs


Typical Wiring- High rise building


Capacity extension via BDU Router



Typical Wiring Riser-out topology

Riser Wiring via DBC4R Riser Distributor






^{*} Above capacity data is based on non-Wi-Fi monitor

DX series Door Stations

Integrated _ Video recording _ IPC connectivity _ Call diverter



Basic villa door station



- Slim style design

 ≤ Slim style design

 < Slim style design

 ≤ Slim style design

 < Slim
- → Zinc alloy panel
- ✓ Metal Call button

- 105 ° view angle
- Auto light up sensor for night view
- Talk and unlock status indicator
- Max.400ma lock consumption
- Surface mounting
- IP54 IK07 rate

Basic villa door station



- □ Big backlit push button

- 105 ° view angle(fisheye is optional)
- Voice prompt
- Auto light up sensor for night view
- Talk and unlock status indicator
- Surface mounting
- IP54 Weatherproof

Access control villa door station

- Stainless Steel housing(316 optional)
- Metal button
- → Pin code for access













- Fisheye Camera(normal 105 degree is optional)
- Auto light up sensor for night view
- Talk and unlock status indicator
- Voice prompt
- Surface by rainy cover or flush mounting
- IP54 IK07 rate

1~4 push-button villa door station



- ✓ Zinc alloy surface.
- Up to 320 RFID access.



Ref. 607F

Flush mountingStainless steel panel

- Fish eye lens (105° lens is optional)
- 1~4 call button is optional(front panel difference)
- Voice prompt
- Flush or Surface mounting for chose
- IP54 Weatherproof

DX821

Integrated door station





NEW

- → Fingerprint proof stainless steel front panel

- Dual network card embedded for Internet connectivity

ANAWLAN Version

46 Version

i j

Ref. DX821 series

821-DX Video Controller

- 170° fisheye lens camera
- High video quality
- Invisible programming button
- Public video memory records
- IP camera connectivity
- Call divert to mobile phone(by LAN, WALAN, 4G)
- XD-APP control for configuring and management
- Flush or Surface mounting for chose
- IP54 Weatherproof

Modularized _ Max.32 call buttons



DT821-Main Modules

A/V module _ call button module




Ref. 821/VD Video module



Ref. 821/AD Audio module







Ref. 821/M-1-2-3-4 button modules are also suitable for 821–DX series

Ref. 821/BL Blank module

170° fisheye Camera Led status indication White led auto-sensor Voice prompt


Led status indication White led auto-sensor Voice prompt


Physical push button with backlit Stainless steel with anti-fingerprint Nameplates with backlit

DT821-Functional Modules


Display RFID Information Keypad













Ref. 821/TFT 3.5" TFT module Ref. 821/DR Digital display & proximity reader Ref. 821/LB Information module Keypad module

Ref. 821/MK

Ref. 821/FP Fingerprint module Ref. 821/T5 Display module & proximity reader

3.5" TFT screen Name-list Calling Logo advertisement Operation method

RFID reader EM &MI fare Digital display tube PMMA panel

Luminous plate Light sense

Mechanical keypad Pin code access Backlit display Calling button module Mechanical keypad Pin code access Backlit display

5"TFT display Touch screen EM & My fare reader

Audio phone

Handset, hands free




- Max.128 audio phone in full audio system
- In-out diagram w/o floor distributor in audio only system
- Can be mix-installed with video intercom

Basic project-monitor

Slim _ OSD display _ Perfect for project





Ref. DT433 Ref. DT17S

- 4.3 inch _ Slim _ Wall mounting w/o bracket
- 7 inch _ Silver sensor button _ Multi languages
- * IP camera surveillance & Video memory view & Call divert to mobile phone (by work with DX door stations)

Basic standard-monitor

Slim _ OSD/Icon display _ Europe-style





Ref. DT471 Ref. DT437


- 4.3 inch _ OSD menu _ Multi languages
- 7 inch _ Touch screen operation _ Color icon menu
- Handset add-on for chose(bigger bracket)



• * IP camera surveillance & Video memory view & Call divert to mobile phone (by work with DX door stations)

Wi-Fi monitor with memory

HD screen _ IPC integration _ Memory _ Call transfer



Ref. DX471S Ref. DX482

- 7" TFT HD Screen (1280*600pixels) _ Wider view angle _ Touch screen
- 720P Video recording _ 3~10s memory against with or w/o SD card
- IP camera connect_ PIP & Quad split display
- Wi-Fi connectivity _ Call divert with VDP Connect APP

Wi-Fi monitor with memory

HD screen _ IPC integration _ Memory _ Call transfer



Ref. DX470

- 7" TFT IPS Screen(1280*600) _ Wider view angle _ Touch screen
- Video recording _ Landscape & Portrait display under same bracket
- IP camera connecting _ PIP & Quad split display
- Wi-Fi connectivity _ Call divert with VDP Connect APP

APP Solution for Users


Call answer _ Door & Camera surveillance _ Lock release



VDP Connect app

Used for two wire and IP system

- Max.5 mobile phones ring simultaneously
- Monitor screen on during diverting
- Free of email registration
- IOS and Android
- Privacy protection
- Multi languages



APP Solution for Installers

Tool management _ Cell phone control _ Wireless connection



XD Device APP

Used for two wire DX door stations







Device Details
















- Remotely control Door station from APP \vee
- V **Fast configuration and System Management**
- Wire or Wireless network connections(Hotspot, LAN, WLAN) \vee

- Service list:
 - General info of device
 - Network configure IP camera configure
 - Firmware online update
 - · Access card & Pin code management
 - Shell command menu for collaboration

OEM customization & ODM development



INFO@V-TEC.COM.CN

WWW.V-TEC.CN

What's new:

https://2easy-wiki.atlassian.net/wiki/spaces/2EASYWIKI/overview