

BATTERIES FROM YUASA



Yuasa has applied over 80 years of experience in lead acid battery technology in the production of NP type batteries. There is an extensive choice of different models from the following "application specific" product ranges.

Standard NP

Available in a wide range of sizes to suit general applications.

NPH (50%) and SW (75%)

High performance batteries specially designed for applications requiring high rate discharge, supplying up to 75% more power (watts) for short durations when compared to conventional NP models.

NPL and RE/REL

The extended service life version of the NP designed for normal standby and float service applications. FR option NPLs to BS6290 part 4. The new REL range offers 15 year design life.

NPC

Specifically designed to suit the arduous requirements of cyclic applications allowing increased cycle life (at least double that of conventional types).

Other Products

Other products and services are available, these include VRLA up to 3300 Ah, small capacity NiCads and NiMH, battery racks / cabinets and installations. Call your local Yuasa Office for further details.

Battery Chargers

A wide range of battery chargers is available covering all the battery types available from Yuasa. Please contact our sales office for details.

Issue date 01.10.01

EUROPEAN SALES & MARKETING NETWORK

YUASA BATTERIES FRANCE SA

Centre D'Affaires Evolic
14 Rue de Bruxelles
38070 Saint-Quentin Fallavier
France
Tel: 00334 749 59090
Fax: 00344 749 59091
Website: www.ybuk.co.uk

YUASA BATTERY (EUROPE) GMBH

Wanheimer Str.47
D-40472 Dusseldorf
Germany
Tel: 0049 211 417900
Fax: 0049 211 4179011
Website: www.ybuk.co.uk



Yuasa batteries produced in the UK are manufactured to ISO 9002:1994. Our customers can, therefore, be assured that when they choose Yuasa, they are choosing a power source manufactured to the highest attainable quality standard.

YUASA

NP RANGE

Model	Nominal voltage (v)	Nominal Capacity (20 hr) (Ah)	Weight Approx. (Kg)	Dimensions		
				L (mm)	W (mm)	H (mm)
NP 4.2-4	4	3.8	0.56	47	35.5	119
NP1-6	6	1.0	0.25	51	42.5	54.5
NP1.2-6	6	1.2	0.31	97	25	54.5
NP2.8-6	6	2.8	0.59	134	34	64
NP3-6	6	3.0	0.65	134	34	64
NP4-6	6	4.0	0.85	70	47	105.5
NP7-6	6	7.0	1.29	151	34	97.5
NP10-6	6	10.0	2	151	50	97.5
NP12-6	6	12.0	2.1	151	50	97.5
NP0.8-12	12	0.8	0.35	96	25	61.5
NP1.2-12	12	1.2	0.59	97	48	55
NP2-12	12	2.0	0.7	150	20	89
NP2.1-12	12	2.1	0.85	178	34	64
NP2.3-12	12	2.3	0.85	178	34	64
NP2.8-12	12	2.8	1.18	134	67	64
NP3.2-12	12	3.2	1.23	134	67	64
NP4-12	12	4.0	1.56	90	70	106
NP7-12	12	7.0	2.8	151	65	98
NP12-12	12	12.0	3.78	151	98	97.5
NP17-12	12	17.0	5.89	181	75	167
NP18-12	12	18.0	6.2	180	76	167
NP24-12	12	24.0	8.99	166	175	125
NP38-12	12	38.0	13.48	197	164	170
NP65-12	12	65.0	22.67	350	166	174

NPC RANGE For Cyclic Applications

NPC 8-6	6	8	1.8	151	50	97.5
NPC17-12	12	17.0	5.89	181	76	167
NPC24-12	12	24.0	8.99	166	175	125
NPC30-12	12	30.0	11.2	195	129	179
NPC38-12	12	38.0	13.52	197	165	170
NPC65-12	12	65.0	23	350	166	174

NPL/RE/REL RANGE Extended Long Life

NPL24-12	12	24.0	8.85	166	175	125
NPL38-12	12	38.0	14.5	197	164	170
NPL65-12	12	65.0	23.8	350	166	174
NPL78-12	12	78.0	27.5	380	166	174
NPL100-12	12	100.0	39	407	173	240
NPL130-6	6	130.0	23.8	350	166	174
NPL200-6	6	200.0	39	398	176	250
RE5-12	12	4.5	1.95	90	70	106
RE7-12	12	6.5	2.75	151	65	98
RE12-12	12	11.0	4.15	151	98	98
REL15-12	12	15	6	181	76	167
REL24-12	12	24	10.5	166	125	175
REL38-12	12	38	14.7	197	166	175
REL65-12	12	65	24.2	311	166	175

NPH/SW RANGE High Rate Discharge

NPH2-12	12	2	0.84	68	51	89
NPH3.2-12	12	3.2	1.4	134	67	67
NPH5-12	12	5	2	90	70	102
NPH12-12	12	12	4.2	151	98	97.5
NPH16-12	12	16	6.2	181	76	167

Yuasa Battery Sales (UK) Ltd

Unit 22 Rassau Industrial Estate, Ebbw Vale, Gwent, NP23 5SD

Tel: 08708 500312

Fax: 08708 500317

Website:

www.yuasa-battery.co.uk

Registered number 1548820

Cat. No.

BfromYSFOct05

E&O.E.