

PR 301
PR 201

Single Door Access
Controllers



CE

roger[®]



RACS

ROGER ACCESS CONTROL SYSTEM

roger®



PR 201



PR 301



Ordering information

PR301	Controller with proximity and PIN reader
PR201	Controller with proximity reader only (without PIN reader)
UT-2	RS232/RS485 communication interface
UT-3	RS232/RS422 communication interface. The communication link created from 2 pcs of UT-3 extends communication distance between to serial devices by 1200m.
UT-4	TCP to serial communication interface. Enables communication with controller or other serial devices through computer network

Technical specification

Operating voltage range	10...16VDC
Current consumption	avg. 80mA
Tamper	normally closed contact, 30V/50mA rated
Cards	UNIQUE type, EM4100/4102 compatible
Reading range	up to 12 cm for ISO type cards(depends on card quality)
Environmental class	Class I - Indoor, temperature +5°C...+40°C
Dimensions	105 X 105 X 31 mm
Weight	175g

PR301 / PR201

Single Door Access Controller with Build-in RFID/PIN Reader

Note: This description refer to firmware version 71.0 or higher.

Features:

- autonomic or networked operation
- built-in proximity reader
- UNIQUE (EM4100/4102) cards
- Card, PIN or Card+PIN identification
- 1 000 card users
- 250 access groups (*)
- 32 time schedules (*)
- 128 periods per schedule (*)
- events recording (*)
- Entry/Exit control (requires second PRT series reader)
- three programmable NO/NC input lines
- one relay output and two transistors outputs
- support for door contact, exit button and alarming device
- rearming output for integration with Intruder Alarm System
- programmed manually or from PC
- RS485 communication interface
- Windows 95/98/NT/2K/Me/XP software
- ABS casing with TAMPER
- CE mark

(*) – available in networked mode only

roger®

tel. +48 55 272 01 32

fax +48 55 272 01 33

e-mail: roger@roger.pl

www.roger.pl

All content, specifications and availability subject to change without prior notice.

