

Cross Line Generator

CPT-9028

SPECIFICATION

Video input	1 Vp-p 75ohm/ BNC
Video output	1 Vp-p 75ohm/ BNC
Horizontal & Vertical line adjustment	Front panel adjustment: Position, Size, Center, Internal adjustment: Width
Level status	Cross line white to black adjustment
Selection switch	Button type
Ambient temperature	-10°C to 50°C
Ambient humidity	0% to 95% relative, non-condensing
Casing structure	Aluminum front panel, Heavy duty steel with black baked enamel finishing.
Power consumption	AC110V / 220V, 50 Hz / 60 Hz, 1 W
Dimension & weight	210(W) x 44(H) x 240(D) mm, 1 Kg.



Features & Characteristic:

- * Sophisticated cross line generator by trimmer adjustment for vertical & horizontal display.
- * Bright to dark line adjustment
- * Video signal measurement
- * Application: Printing , Medical, electronic checking

Digital
Cross Line Generator

CPT-D9028

SPECIFICATION

Video input & output	1 Vp-p 75ohm, S terminal: Y-0.7Vp-p 75Ω / S-0.3 Vp-p 75Ω
Horizontal & Vertical Position adjustment	Front panel 8 steps adjustment DIP switch
Level status	LEFT: Black line, RIGHT: white line
Front panel 3 step switch	CENTER: Flash line when object touch center
Line status	LEFT: Center cross line, other dotted line
Front panel 3 step switch	CENTER: Point mark, other dotted line RIGHT: Full line
Casing structure	Heavy duty steel white backed enamel finish
Ambient Temperature	-10°C to + 50°C, Humidity: 0 to 95%
Power consumption	AC 110V/220V , 50Hz/ 60Hz , 1W
Dimension & weight	210(W) x 44(H) x 240)mm-1Kg



Features & Characteristic:

- * Sophisticated cross-line marking positioning
- * Black line / White line / Dotted line display
- * Center auto flashing display
- * Image measurement
- * Application: Printing , Medical, electronic checking.