

1 channel  
Pan/Tilt/Zoom Remote controller

# CPT-1001K

## SPECIFICATION

<b>Control mode</b>	Joystick: up / down, left / right Zoom in/out , Focus far/near , Iris open/close auto/manual pan , Iris auto/manual
<b>Lens control</b>	Lens voltage DC $\pm 8V \sim \pm 12V / 150 \text{ mA}$ , internal adjustable
<b>Terminal Connector</b>	DIN 6p, Output power voltage same as input voltage, Lens: DIN 5p
<b>Power switch</b>	Front panel , Power LED indicator, Safety protection fuse 1A
<b>Power voltage</b>	AC110V / AC220V, Option(AC24V), 50Hz/60Hz
<b>Casing Structure</b>	Front panel, Metal structure, color black
<b>Ambient temperature</b>	Operation: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ , Storage: $-30^{\circ}\text{C} \sim 70^{\circ}\text{C}$
<b>Body Dimension</b>	1U 1/2Size 210(W) ´ 44.5(H) ´ 240(D) mm – 1.2 Kg



5 channels  
Pan/Tilt/Zoom Remote controller

# CPT-1005K

## SPECIFICATION

<b>Channel selection</b>	Turner switching Joystick control: Up / Down, Left / Right
<b>Control mode</b>	Zoom in/out , Focus far/near , Iris open/close auto/manual pan
<b>Lens control</b>	Lens voltage: DC $\pm 8V \sim \pm 12V / 150 \text{ mA}$ , Internal adjustable
<b>Terminal Connector</b>	DIN 6p, Output voltage same as input voltage, Lens: DIN 5p
<b>Power switch</b>	Front panel , Power LED indicator, Safety Fuse: 1A
<b>Power voltage</b>	AC110V / AC220V, Option (AC24V), 50Hz/60Hz
<b>Casing Structure</b>	Aluminum front panel, Metallic structure, color black
<b>Ambient temperature</b>	operation: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ , Storage: $-30^{\circ}\text{C} \sim 70^{\circ}\text{C}$
<b>Body dimension</b>	1U Full Size, 410(W) ´ 44.5(H) ´ 240(D) mm – 4 Kg

