

# Extend PoE Switch

GNT-69P62E6  
GNT-6FP62E6

- Total 60W Power Supply
- 4 ports PoE
- 2 ports Uplink

## Product Features


- AI Watchdog Function
- 6KV Lightning & 8KV ESD Protection
- Support bt 60W High Power
- Compact Design, Competitive Solution

## Ports Description




- ① 100Mbps PoE Ports
- ② bt 60W Power Ports
- ③ 100Mbps Uplink Ports

## Dimension (mm)



## Installation Diagram



## Specifications

Model	GNT-69P62E6 / GNT-6FP62E6
Ports	PoE (1~3):10/100Mbps PoE ports (RJ45) PoE (4):10/100Mbps PoE port (RJ45),Support bt 60W High Power LAN (1~2):10/100Mbps uplink ports (RJ45)
Transmission Rate	200Mbps Full Duplex; 10 or 100Mbps Half Duplex
Transmission Distance	130m(Max Cascade 2~4 Times)
Performance Specification	Bandwidth:1.2Gbps
	Network Latency (10 to 100Mbps): $\leq 16\mu s$ (use the 64byte package size)
	MAC address table: 2K
	The F rame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port
Networking Standard	IEEE 802.3i 10BASE-T
	IEEE 802.3u 100BASE-TX
	IEEE 802.3x Flow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Total $\leq 60W$ AI Watchdog: Port 1~4 Power Output: PoE1~3 Port:1/2(+52V),3/6(GND) $\leq 30W$ PoE 4 Port:1245(+52V),3678(GND) Compatible1/2(+52V),3/6(GND) $\leq 60W$
Protection Level	Lightning Protection:6KV ESD Protection:8KV
Physical Specifications	Size(L*W*H): 130*67*26mm, Weight: 0.45KG Indoor 228*168*68mm, Weight: 1.0KG Outdoor
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	User Manual